
DELTALIGHT




SUPERNOVA FLAT 95 PRISMATIC SMOOTH UP 930 DIM5

REFERENCE 20638 9305 B

AVAILABLE IN
BLACK 20638 9305 B
WHITE 20638 9305 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	16.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY 2100mA

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 1860: LED cluster 79,4W / CRI>90 (R9: 68) / 3000K / 11477lm Or @ 1300: LED cluster 54,2W / CRI>90 (R9: 68) / 3000K / 8273lm
TM-30 VALUES	Rf: 89 / Rg: 97 @ 1300: Rf: 89 / Rg: 97
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 1860: 11477lm // 79,4W // 144lm/W Or @ 1300: 8273lm // 54,2W // 153lm/W
LED TECHNICS (LUMINAIRE)	@ 1860: 8849lm // 91,3W // 97lm/W Or @ 1300: 6378lm // 62,3W // 102lm/W

Options

SUSPENSION SET 25 DIM 3m
CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT


SUPERNOVA FLAT 95 PRISMATIC SMOOTH UP 930 DIM5

20638 9305 B

For detailed installation instructions, please consult the manual : **20638_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W




203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B

204 00 62 W COVERSET R 62 W







204 00 90 ANO COVERSET R 90 ANO

DELTALIGHT

SUPERNOVA FLAT 95 PRISMATIC SMOOTH UP 930 DIM5

20638 9305 B

	204 00 90 B	COVERSET R 90 B	☐
	204 00 90 W	COVERSET R 90 W	☐
	**204 00 100 ANO**	COVERSET R 100 ANO	☐
	204 00 100 B	COVERSET R 100 B	☐
	204 00 100 W	COVERSET R 100 W	☐
	**204 62 62 ANO**	COVERSET S 62 ANO	☐
	204 62 62 B	COVERSET S 62 B	☐
	204 62 62 W	COVERSET S 62 W	☐
	**204 80 80 ANO**	COVERSET S 80 ANO	☐
	204 80 80 B	COVERSET S 80 B	☐
	204 80 80 W	COVERSET S 80 W	☐
	**204 90 90 ANO**	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐
	204 90 90 W	COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA FLAT 95 PRISMATIC SMOOTH UP 930 DIM5


20638 9305 B

Suspension parts




274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B ☐

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W ☐



328 25 43 ED SUSPENSION SET 25 DIM 3m ☐



328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B ☐

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W ☐

Electric connection parts



15225 0360 B CONNECTION ST B ☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W ☐

Notes: