
DELTALIGHT




# FRAGMA M 93014 ADM DIM1

**REFERENCE** 23611 9311 B

AVAILABLE IN
**BLACK** 23611 9311 B
**WHITE** 23611 9311 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Mains voltage track Mains voltage track mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 1.3 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | 9 x LENS SP-14°<br>INCL.DIMMABLE LED POWER SUPPLY 900mA-DC<br>3F MULTI ADAPTER |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | 1-10V |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, EAC, ENEC, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 23,4W / CRI>90 (R9: 64) / 3000K / 2654lm |
| **TM-30 VALUES** | Rf: 92 / Rg: 99 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 150000 |
| **BEAMANGLE** | 14° |
| **LED TECHNICS (LIGHT SOURCE)** | 2654lm // 23,4W // 113lm/W |
| **LED TECHNICS (LUMINAIRE)** | 2123lm // 27W // 79lm/W |

**Requirements**

TRACK 3F DIM

**Options**

FRAGMA 3X3 BEAM LENS

**Accessories**

FRAGMA 3X3 ACCESSORIES

# FRAGMA M 93014 ADM DIM1

23611 9311 B

For detailed installation instructions, please consult the manual : **23611_XXX1_HAND.pdf**


DELTALIGHT

# FRAGMA M 93014 ADM DIM1


23611 9311 B

## FINISH YOUR SPECIFICATION


### Light altering devices





**23613 0020** FRAGMA M BEAM LENS 26°





**23613 0050** FRAGMA M BEAM LENS 47°





**23613 0080** FRAGMA M SOFTENING LENS





**23613 0120** FRAGMA M LINEAR SPREAD LENS





**23613 0170** FRAGMA M WALLWASH LENS




**23613 0200 B** FRAGMA M FLAPS B




**23613 0230 B** FRAGMA M HONEYCOMB B




**23613 0260 B** FRAGMA M RASTER B

DELTALIGHT

# FRAGMA M 93014 ADM DIM1

23611 9311 B

## COMPATIBLE TRACKS

| TRACK 3F DIM H | | | Available Colours |
|---|---|---|---|
| **200 14 410** TRACK 3F DIM H 1m | 1000 m | 1.6 kg | |
| **200 14 420** TRACK 3F DIM H 2m | 2000 m | 3.2 kg | |
| **200 14 430** TRACK 3F DIM H 3m | 3000 m | 4.8 kg | |

| TRACK 3F DIM IN | | | Available Colours |
|---|---|---|---|
| **200 13 410** TRACK 3F DIM IN 1m | 1000 m | 1.2 kg | |
| **200 13 420** TRACK 3F DIM IN 2m | 2000 m | 2.4 kg | |
| **200 13 430** TRACK 3F DIM IN 3m | 3000 m | 3.5 kg | |

| TRACK 3F DIM ON | | | Available Colours |
|---|---|---|---|
| **200 12 410** TRACK 3F DIM ON 1m | 1000 m | 1.1 kg | |
| **200 12 420** TRACK 3F DIM ON 2m | 2000 m | 2.1 kg | |
| **200 12 430** TRACK 3F DIM ON 3m | 3000 m | 3.1 kg | |

Notes: