





## POLESANO 940 MEDIUM

43 11 942 A-B

AVAILABLE IN

**ALU GREY-BLACK** 43 11 942 A-B

**ANTHRACITE-BLACK** 43 11 942 N-B



[View on website](#)



| General info                         |                                                                                                                                                                                                  |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                             | outdoor                                                                                                                                                                                          |
| INSTALLATION                         | Pole Pole top                                                                                                                                                                                    |
| INGRESS PROTECTION                   | IP66                                                                                                                                                                                             |
| PROTECTION AGAINST MECHANICAL IMPACT | IK08                                                                                                                                                                                             |
| WEIGHT (KG)                          | 5                                                                                                                                                                                                |
| ADJUSTABILITY                        | 360° swiveling, 360° rotatable                                                                                                                                                                   |
| INFORMATION                          | 16 x LENS FL-47°<br>INCL.DIMMABLE LED POWER SUPPLY 900mA-DC<br>$\lambda > 0,9$<br>Inrush current : 32A - 355µs @ 230V-AC<br>Max. 10 units on circuit breaker B 16A @ 230V-AC (13 units on B 20A) |
| Electrical info                      |                                                                                                                                                                                                  |
| ELECTRICAL                           | 220-240V / 0 50-60Hz                                                                                                                                                                             |
| CLASS                                | I                                                                                                                                                                                                |
| POWER SUPPLY                         | YES                                                                                                                                                                                              |
| DIM TYPE                             | DALI                                                                                                                                                                                             |
| ENERGY CLASS                         | F                                                                                                                                                                                                |
| CERTIFICATES                         | CB, EAC, ENEC, ENEC+, RCM                                                                                                                                                                        |
| Lightsource info                     |                                                                                                                                                                                                  |
| LIGHTSOURCE NAME                     | LED                                                                                                                                                                                              |
| LIGHTSOURCE                          | LED cluster 41,6W / CRI>90 (R9: 64) / 4000K / 5136lm                                                                                                                                             |
| TM-30 VALUES                         | Rf: 91 / Rg: 100                                                                                                                                                                                 |
| SDCM                                 | SDCM3                                                                                                                                                                                            |
| RISKGROUP                            | RG2                                                                                                                                                                                              |
| LM80                                 | L80 > 150000                                                                                                                                                                                     |
| BEAMANGLE                            | 47°                                                                                                                                                                                              |
| LED TECHNICS (LIGHT SOURCE)          | 5136lm // 41,6W // 123lm/W                                                                                                                                                                       |
| LED TECHNICS (LUMINAIRE)             | 3699lm // 47,8W // 77lm/W                                                                                                                                                                        |

### Remarks

[Take a look at the POLESANO brochure](#)

### Requirements

POLESANO POLE

### Accessories


HONEYCOMB S105

LINEAR SPREAD LENS S105


For detailed installation instructions, please consult the manual : [43\\_XX\\_XXX-431\\_X00\\_XX1\\_\(X\)X1\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices




**431 03 01 B** HONEYCOMB S105 B

☐

**431 03 02** LINEAR SPREAD LENS S105

☐


Pole



**431 400 111 11 A** POLESANO 4M - 1 ANCHORED A

☐


**431 400 111 11 N** POLESANO 4M - 1 ANCHORED N

☐

**431 400 111 21 A** POLESANO 4M - 2 ANCHORED A

☐

**431 400 111 21 N** POLESANO 4M - 2 ANCHORED N

☐

**431 400 111 31 A** POLESANO 4M - 3 ANCHORED A

☐








**431 400 111 31 N** POLESANO 4M - 3 ANCHORED N

☐

# DELTALIGHT

## POLESANO 940 MEDIUM







43 11 942 A-B

|                                                                                    |                          |                              |                          |
|------------------------------------------------------------------------------------|--------------------------|------------------------------|--------------------------|
|    | <b>431 400 111 41 A</b>  | POLESANO 4M - 4 ANCHORED A   | <input type="checkbox"/> |
|                                                                                    | <b>431 400 111 41 N</b>  | POLESANO 4M - 4 ANCHORED N   | <input type="checkbox"/> |
|    | <b>431 400 111 211 A</b> | POLESANO 4M - 21L ANCHORED A | <input type="checkbox"/> |
|                                                                                    | <b>431 400 111 211 N</b> | POLESANO 4M - 21L ANCHORED N | <input type="checkbox"/> |
|    | <b>431 400 111 221 A</b> | POLESANO 4M - 22L ANCHORED A | <input type="checkbox"/> |
|                                                                                    | <b>431 400 111 221 N</b> | POLESANO 4M - 22L ANCHORED N | <input type="checkbox"/> |
|  | <b>431 400 221 11 A</b>  | POLESANO 4M - 1 BASE A       | <input type="checkbox"/> |
|                                                                                    | <b>431 400 221 11 N</b>  | POLESANO 4M - 1 BASE N       | <input type="checkbox"/> |
|  | <b>431 400 221 21 A</b>  | POLESANO 4M - 2 BASE A       | <input type="checkbox"/> |
|                                                                                    | <b>431 400 221 21 N</b>  | POLESANO 4M - 2 BASE N       | <input type="checkbox"/> |
|  | <b>431 400 221 31 A</b>  | POLESANO 4M - 3 BASE A       | <input type="checkbox"/> |
|                                                                                    | <b>431 400 221 31 N</b>  | POLESANO 4M - 3 BASE N       | <input type="checkbox"/> |
|  | <b>431 400 221 41 A</b>  | POLESANO 4M - 4 BASE A       | <input type="checkbox"/> |








# DELTALIGHT

## POLESANO 940 MEDIUM

43 11 942 A-B

|                                                                                    |                                 |                            |                          |
|------------------------------------------------------------------------------------|---------------------------------|----------------------------|--------------------------|
|                                                                                    | <b><u>431 400 221 41 N</u></b>  | POLESANO 4M - 4 BASE N     | <input type="checkbox"/> |
|    | <b><u>431 400 221 211 A</u></b> | POLESANO 4M - 21L BASE A   | <input type="checkbox"/> |
|                                                                                    | <b><u>431 400 221 211 N</u></b> | POLESANO 4M - 21L BASE N   | <input type="checkbox"/> |
|    | <b><u>431 400 221 221 A</u></b> | POLESANO 4M - 22L BASE A   | <input type="checkbox"/> |
|                                                                                    | <b><u>431 400 221 221 N</u></b> | POLESANO 4M - 22L BASE N   | <input type="checkbox"/> |
|   | <b><u>431 600 121 11 A</u></b>  | POLESANO 6M - 1 ANCHORED A | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 121 11 N</u></b>  | POLESANO 6M - 1 ANCHORED N | <input type="checkbox"/> |
|  | <b><u>431 600 121 21 A</u></b>  | POLESANO 6M - 2 ANCHORED A | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 121 21 N</u></b>  | POLESANO 6M - 2 ANCHORED N | <input type="checkbox"/> |
|  | <b><u>431 600 121 31 A</u></b>  | POLESANO 6M - 3 ANCHORED A | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 121 31 N</u></b>  | POLESANO 6M - 3 ANCHORED N | <input type="checkbox"/> |
|  | <b><u>431 600 121 41 A</u></b>  | POLESANO 6M - 4 ANCHORED A | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 121 41 N</u></b>  | POLESANO 6M - 4 ANCHORED N | <input type="checkbox"/> |

## POLESANO 940 MEDIUM


|                                                                                    |                                 |                              |                          |
|------------------------------------------------------------------------------------|---------------------------------|------------------------------|--------------------------|
|    | <b><u>431 600 121 211 A</u></b> | POLESANO 6M - 21L ANCHORED A | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 121 211 N</u></b> | POLESANO 6M - 21L ANCHORED N | <input type="checkbox"/> |
|    | <b><u>431 600 121 221 A</u></b> | POLESANO 6M - 22L ANCHORED A | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 121 221 N</u></b> | POLESANO 6M - 22L ANCHORED N | <input type="checkbox"/> |
|    | <b><u>431 600 321 11 A</u></b>  | POLESANO 6M - 1 BASE A       | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 321 11 N</u></b>  | POLESANO 6M - 1 BASE N       | <input type="checkbox"/> |
|  | <b><u>431 600 321 21 A</u></b>  | POLESANO 6M - 2 BASE A       | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 321 21 N</u></b>  | POLESANO 6M - 2 BASE N       | <input type="checkbox"/> |
|  | <b><u>431 600 321 31 A</u></b>  | POLESANO 6M - 3 BASE A       | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 321 31 N</u></b>  | POLESANO 6M - 3 BASE N       | <input type="checkbox"/> |
|  | <b><u>431 600 321 41 A</u></b>  | POLESANO 6M - 4 BASE A       | <input type="checkbox"/> |
|                                                                                    | <b><u>431 600 321 41 N</u></b>  | POLESANO 6M - 4 BASE N       | <input type="checkbox"/> |
|  | <b><u>431 600 321 211 A</u></b> | POLESANO 6M - 21L BASE A     | <input type="checkbox"/> |

# DELTALIGHT

## POLESANO 940 MEDIUM

43 11 942 A-B

**431 600 321 211 N** POLESANO 6M - 21L BASE N

☐

**431 600 321 221 A** POLESANO 6M - 22L BASE A

☐

**431 600 321 221 N** POLESANO 6M - 22L BASE N

☐

Notes: