
DELTALIGHT




SPYCO ON 3 92733 DIM8

REFERENCE 414 353 813 922 ED8 W

AVAILABLE IN
BLACK 414 353 813 922 ED8 B
WHITE 414 353 813 922 ED8 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	3 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	2259lm // 17,4W // 129lm/W
LED TECHNICS (LUMINAIRE)	1622lm // 20W // 81lm/W

Requirements

SPY TUBE S

For detailed installation instructions, please consult the manual : **414_353_813_XXX_ED8_HAND.pdf**


DELTALIGHT

SPYCO ON 3 92733 DIM8

414 353 813 922 ED8 W

FINISH YOUR SPECIFICATION

Finish your product

	**414 02 00 B**	SPY TUBE S B	☐
	414 02 00 FBR	SPY TUBE S FBR	☐
	414 02 00 FG	SPY TUBE S FG	☐
	414 02 00 MMAT	SPY TUBE S MMAT	☐
	414 02 00 SG	SPY TUBE S SG	☐
	414 02 00 W	SPY TUBE S W	☐

Notes: