





MULTINOVA 355 SOFT 930 DIM5

REFERENCE 28067 9005 GC

AVAILABLE IN
BLACK 28067 9005 B
GOLD COLOURED 28067 9005 GC
WHITE 28067 9005 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	14
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm ²
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 32,3W / CRI>90 (R9: 50) / 3000K-1800K / 4567lm)
TM-30 VALUES	Rf: 89,4 / Rg: 98,6
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	13701lm // 96,9W // 141lm/W
LED TECHNICS (LUMINAIRE)	11042lm // 111,4W // 99lm/W


Options

CABLE BASE R / S
COVERSET R 62-90-100
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



For detailed installation instructions, please consult the manual : [28067_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	<u>203 99 55 ANO</u> CABLE BASE R ANO	☐
	<u>203 99 55 B</u> CABLE BASE R B	☐
	<u>203 99 55 W</u> CABLE BASE R W	☐
	<u>203 99 56 ANO</u> CABLE BASE S ANO	☐
	<u>203 99 56 B</u> CABLE BASE S B	☐
	<u>203 99 56 W</u> CABLE BASE S W	☐


Coversets

	<u>204 00 62 ANO</u> COVERSET R 62 ANO	☐
	<u>204 00 62 B</u> COVERSET R 62 B	☐
	<u>204 00 62 W</u> COVERSET R 62 W	☐
	<u>204 00 90 ANO</u> COVERSET R 90 ANO	☐
	<u>204 00 90 B</u> COVERSET R 90 B	☐
	<u>204 00 90 W</u> COVERSET R 90 W	☐

DELTALIGHT

MULTINOVA 355 SOFT 930 DIM5

28067 9005 GC



204 00 100 ANO COVERSET R 100 ANO

☐


204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐


Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B


☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes:

DELTALIGHT

MULTINOVA 355 SOFT 930 DIM5

28067 9005 GC