



OML50 - LED ARRAY DU TW 1312mm 950 DIM5

31048 9005



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.7
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN @ 2700K: LED cluster 29,8W / CRI>90 (R9: 50) / 2700K-5000K / 3904lm UP @ 2700K: LED cluster 14,9W / CRI>90 (R9: 50) / 2700K-5000K / 1952lm Or DOWN @ 5000K: LED cluster 27W / CRI>90 (R9: 50) / 2700K-5000K / 4672lm UP @ 5000K: LED cluster 13,5W / CRI>90 (R9: 50) / 2700K-5000K / 2336lm
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN @ 2700K: 3904lm // 29,8W // 131lm/W UP @ 2700K: 1952lm // 14,9W // 131lm/W Or DOWN @ 5000K: 4672lm // 27W // 173lm/W UP @ 5000K: 2336lm // 13,5W // 173lm/W

Opties

WIRELESS CONTROL DIM5

Notes:

DELTALIGHT

OML50 - LED ARRAY DU TW 1312mm 950 DIM5

31048 9005