





MINI DEEP RINGO II OK 93037

REFERENCE 19425 9330 BRBB

AVAILABLE IN
BLACK 19425 9330 B
BRUSHED ALU 19425 9330 BRA
BRUSHED ANTHRACITE 19425 9330 BRAT
BRUSHED BROWN BRONZE 19425 9330 BRBB
BRUSHED COPPER 19425 9330 BRCU
BRUSHED GOLD 19425 9330 BRG
BRUSHED OLD BRONZE 19425 9330 BROB
CREAM 19425 9330 CR
FLEMISH BRONZE 19425 9330 FBR
FLEMISH GOLD 19425 9330 FG
WHITE 19425 9330 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 71
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 30° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-37° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	37°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	724lm // 9,9W // 73lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

MINI DEEP RINGO II OK 93037

19425 9330 BRBB


For detailed installation instructions, please consult the manual : [19425_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-









FINISH YOUR SPECIFICATION

Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐











MINI DEEP RINGO II OK 93037

19425 9330 BRBB

LED power supplies		# of Fixtures
<div><div></div><div># of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div>		Min current Max current
<div><div></div><div><div>300 48 350 ED1</div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1</div><div>Dimtype: 1-10V</div><div>Cutout dimension (mm): 30</div></div></div>	2	☐
<div><div></div><div><div>300 48 350 ED5</div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5</div><div>Dimtype: DALI</div><div>Cutout dimension (mm): 45</div></div></div>	2	☐
<div><div></div><div><div>300 48 350 MDL</div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 30</div></div></div>	2	☐
<div><div></div><div><div>300 48 350 WDL</div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL</div><div>Dimtype: WDL = wireless dimmable</div><div>Cutout dimension (mm): 45</div></div></div>	2	☐
<div><div></div><div><div>300 48 500 ED1</div><div>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1</div><div>Dimtype: 1-10V</div><div>Cutout dimension (mm): 30</div></div></div>	2	☐
<div><div></div><div><div>300 48 500 ED5</div><div>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5</div><div>Dimtype: DALI</div><div>Cutout dimension (mm): 45</div></div></div>	2	☐
<div><div></div><div><div>300 48 500 MDL</div><div>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 30</div></div></div>	2	☐
<div><div></div><div><div>300 48 500 WDL</div><div>LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL</div><div>Dimtype: WDL = wireless dimmable</div><div>Cutout dimension (mm): 45</div></div></div>	2	☐











MINI DEEP RINGO II OK 93037

19425 9330 BRBB

	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: mains (phase cut-off) or push button Cutout dimension (mm): 56	2 2	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	4(4) 4(4)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	3(2) 2(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	2 -	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	2(2) 2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	2->6(6) 6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	2(2) 2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) 2(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	3->4 2->4	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	2 2	☐

MINI DEEP RINGO II OK 93037






19425 9330 BRBB

	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	3 3	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	3 3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	4(4) 4(3)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	3 3	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	1	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	2->2	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	2->3	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	2 2	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	1	☐

DELTALIGHT

MINI DEEP RINGO II OK 93037

19425 9330 BRBB

	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	2(2)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐

Notes: