



SUPERLOOP SLIM IN 90 SBL 927

20573 9200 FBR

AVAILABLE IN



NOIR 20573 9200 B

FLEMISH BRONZE 20573 9200 FBR

FLEMISH GOLD 20573 9200 FG

COULEUR OR 20573 9200 GC

BLANC 20573 9200 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.9
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 700-900mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,2-39W / CRI>90 (R9: 59) / 2700K / 3888-5160lm
SDMC	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	5160lm // 39W // 132lm/W
LED TECHNICS (LUMINAIRE)	2285lm // 44,8W // 51lm/W

Requirements

LED POWER SUPPLY 700 / 900mA-DC DIM
SUPERLOOP POWERBOX L/H 700mA
SUPERLOOP POWERBOX H 900mA


Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20573_XXX0_HAND.pdf](#)



FINISH YOUR SPECIFICATION

le cable d'alimentation

	<u>203 99 55 ANO</u> CABLE BASE R ANO	☐
	<u>203 99 55 B</u> CABLE BASE R B	☐
	<u>203 99 55 W</u> CABLE BASE R W	☐
	<u>203 99 56 ANO</u> CABLE BASE S ANO	☐
	<u>203 99 56 B</u> CABLE BASE S B	☐
	<u>203 99 56 W</u> CABLE BASE S W	☐

Power box


of Fixtures

 web2print_power_supply_info_box		Min current Max current	
	<u>321 55 207 ED1 B</u> SUPERLOOP POWERBOX L 700mA DIM1 B	1	
Dimtype: 1 à 10 V			
	<u>321 55 207 ED1 W</u> SUPERLOOP POWERBOX L 700mA DIM1 W	1	
	<u>321 55 307 ED5 B</u> SUPERLOOP POWERBOX H8 700mA DIM5 B	1	
Dimtype: DALI			
	<u>321 55 307 ED5 W</u> SUPERLOOP POWERBOX H8 700mA DIM5 W	1	

DELTALIGHT

SUPERLOOP SLIM IN 90 SBL 927

20573 9200 FBR



20548 0015 B

SUPERLOOP POWERBOX H9 900mA DIM5 B

1

☐

Dimtype: DALI

20548 0015 W

SUPERLOOP POWERBOX H9 900mA DIM5 W

1

☐


les alimentations led

of Fixtures



web2print_power_supply_info_box

Min current | Max current



300 90 128


LED POWER SUPPLY 700mA-DC / 36W DIM1

1

☐

Dimtype: 1 à 10 V

Cutout dimension (mm): 54



300 90 129


LED POWER SUPPLY 900mA-DC / 60W DIM5

1

☐

Dimtype: DALI

Cutout dimension (mm): 84



300 90 131

LED POWER SUPPLY 700mA-DC / 38W DIM5


1

☐

Dimtype: DALI

Cutout dimension (mm): 54

les sets pour recouvrement plafond



204 00 62 ANO

COVERSET R 62 ANO

☐


204 00 62 B

COVERSET R 62 B

☐

204 00 62 W

COVERSET R 62 W

☐

204 00 90 ANO

COVERSET R 90 ANO

☐

204 00 90 B





COVERSET R 90 B

☐

DELTALIGHT

SUPERLOOP SLIM IN 90 SBL 927

20573 9200 FBR


	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT


SUPERLOOP SLIM IN 90 SBL 927

20573 9200 FBR

les accessoires de suspension

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0340 B SUSPENSION ST B	☐
Cutout dimension (mm): 27		
	15225 0340 W SUSPENSION ST W	☐

les accessoires pour connexions électriques

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
	15225 0360 W CONNECTION ST W	☐

Notes: