



## M26L - SPY 391 SOFT 93040 MDL

23437 9030 PB

AVAILABLE IN

**BLACK** 23437 9030 B

**BRUSHED ALU** 23437 9030 BRA

**BRUSHED ANTHRACITE** 23437 9030 BRAT

**BRUSHED COPPER** 23437 9030 BRCU

**BRUSHED GOLD** 23437 9030 BRG

**BRUSHED OLD BRONZE** 23437 9030 BROB

**FLEMISH BRONZE** 23437 9030 FBR

**FLEMISH GOLD** 23437 9030 FG

**GOLD COLOURED** 23437 9030 GC

**PIANO BLACK** 23437 9030 PB

**WHITE** 23437 9030 W



[View on website](#)



### General info

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| <b>LOCATION</b>           | indoor                                            |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted    |
| <b>INGRESS PROTECTION</b> | IP20                                              |
| <b>WEIGHT (KG)</b>        | 0.3                                               |
| <b>ADJUSTABILITY</b>      | 0° to 85° swiveling, 360° rotatable               |
| <b>INFORMATION</b>        | REFLECTOR WFL-40°<br>EXCL.LED POWER SUPPLY 48V-DC |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | F                                  |
| <b>CERTIFICATES</b> | EPD                                |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm |
| <b>TM-30 VALUES</b>                | rf: 90 / Rg: 99                                      |
| <b>SDCM</b>                        | SDCM2                                                |
| <b>RISKGROUP</b>                   | RG1                                                  |
| <b>LM80</b>                        | L90B10 > 50000                                       |
| <b>BEAMANGLE</b>                   | 40°                                                  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 623lm // 6W // 105lm/W                               |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 505lm // 6,9W // 73lm/W                              |

### Requirements

SPY 39 TUBE  
LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [23437\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply

#### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0030** SMART 48 MODULATOR PLUG-IN WD

16

Dimtype: WDL = wireless dimmable

#### SMART 48

#### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

16

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

16

Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: non-dimmable

# DELTALIGHT

## M26L - SPY 391 SOFT 93040 MDL


23437 9030 PB

|                                                                                  |                                                         |    |                          |
|----------------------------------------------------------------------------------|---------------------------------------------------------|----|--------------------------|
|  | <b>300 89 48 240</b> LED POWER SUPPLY 48V-DC / 240W DIN | 20 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
|  | <b>21012 0230</b> LED POWER SUPPLY 48V-DC / 100W        | 8  | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
| Cutout dimension (mm): 40                                                        |                                                         |    |                          |
|  | <b>21012 0240</b> LED POWER SUPPLY 48V-DC / 200W        | 17 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
| Cutout dimension (mm): 40                                                        |                                                         |    |                          |

### Finish your product

|                                                                                     |                                       |                          |
|-------------------------------------------------------------------------------------|---------------------------------------|--------------------------|
|    | <b>24144 0010 B</b> SPY 39 TUBE B     | <input type="checkbox"/> |
|                                                                                     | <b>24144 0010 FBR</b> SPY 39 TUBE FBR | <input type="checkbox"/> |
|                                                                                     | <b>24144 0010 FG</b> SPY 39 TUBE FG   | <input type="checkbox"/> |
|                                                                                     | <b>24144 0010 GC</b> SPY 39 TUBE GC   | <input type="checkbox"/> |
|                                                                                     | <b>24144 0010 W</b> SPY 39 TUBE W     | <input type="checkbox"/> |
|  | <b>24144 0070</b> SPY 39 TUBE SBL     | <input type="checkbox"/> |

## COMPATIBLE COMPOSABLES

| SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)                                    | Available Colours                                                                                                                                                           |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |   |
| <b>23358 0000</b> SLM26L - PROFILE                                                  |                                                                                                                                                                             |


# DELTALIGHT

## M26L - SPY 391 SOFT 93040 MDL


23437 9030 PB



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m



**23358 0030** SLM26L - PROFILE 3m



Notes: