
DELTALIGHT




NOCTA SQ155 DOWN-UP VWFL 930 DIM5

REFERENCE 30128 9305 W

AVAILABLE IN
ALU GREY 30128 9305 A
BLACK 30128 9305 B
FLEMISH BRONZE OUTDOOR 30128 9305 FBRX
ANTHRACITE 30128 9305 N
WHITE 30128 9305 W





View on website

General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.2 x LENS INCL.DIMMABLE LED POWER SUPPLY 350 mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 52) / 3000K / 734lm)
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1468lm // 11,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	896lm // 13,3W // 67lm/W

For detailed installation instructions, please consult the manual : **30128_XXX5_HAND.pdf**

DELTALIGHT

NOCTA SQ155 DOWN-UP VWFL 930 DIM5

30128 9305 W

Notes: