





SUPERLOOP VC 70 SBL 927

REFERENCE 321 507 92 B

AVAILABLE IN
BLACK 321 507 92 B
FLEMISH BRONZE 321 507 92 FBR
FLEMISH GOLD 321 507 92 FG
WHITE 321 507 92 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 500-700mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 21,2-29,2W / CRI>90 (R9: 59) / 2700K / 2916-3870lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3870lm // 29,2W // 132lm/W
LED TECHNICS (LUMINAIRE)	2325lm // 33,6W // 69lm/W

Requirements

LED POWER SUPPLY 500 / 700mA-DC DIM
 SUPERLOOP POWERBOX L 500mA
 SUPERLOOP POWERBOX L/H 700mA

For detailed installation instructions, please consult the manual : [321_507_93_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 90 127 LED POWER SUPPLY 500mA-DC / 27W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 54




300 90 128 LED POWER SUPPLY 700mA-DC / 36W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 54



300 90 131 LED POWER SUPPLY 700mA-DC / 38W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 54


Power box

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




321 55 205 ED1 B SUPERLOOP POWERBOX L 500mA DIM1 B

1

Dimtype: 1-10V

321 55 205 ED1 W SUPERLOOP POWERBOX L 500mA DIM1 W

1



321 55 207 ED1 B SUPERLOOP POWERBOX L 700mA DIM1 B

1

Dimtype: 1-10V


321 55 207 ED1 W SUPERLOOP POWERBOX L 700mA DIM1 W

1

DELTALIGHT

SUPERLOOP VC 70 SBL 927

321 507 92 B

	<u>321 55 307 ED5 B</u> SUPERLOOP POWERBOX H8 700mA DIM5 B	1	☐
	Dimtype: DALI		
	<u>321 55 307 ED5 W</u> SUPERLOOP POWERBOX H8 700mA DIM5 W	1	☐

Notes: