



INFORM R4 C DOWN 93048

26825 9320 FG-B

AVAILABLE IN



BLACK-BLACK 26825 9320 B-B

BLACK-FLEMISH GOLD 26825 9320 B-FG

FLEMISH GOLD-BLACK 26825 9320 FG-B

WHITE-BLACK 26825 9320 W-B

WHITE-WHITE 26825 9320 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° EXCL.LED POWER SUPPLY 700mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 22,9W / CRI>90 (R9: 50) / 3000K / 3504lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	3504lm // 22,9W // 153lm/W
LED TECHNICS (LUMINAIRE)	2926lm // 26,3W // 111lm/W

Requirements

LED POWER SUPPLY 700mA-DC DIM (Remote)
INFORM R POWERBOX D DIM5

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [26825_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Power box

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	26810 0015 B INFORM R POWERBOX D DIM5 B	1 ☐
Dimtype: DALI		
	26810 0015 W INFORM R POWERBOX D DIM5 W	1 ☐

LED power supplies


of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
--	--	---------------------------

DELTALIGHT

INFORM R4 C DOWN 93048

26825 9320 FG-B




300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

1

☐

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5


1

☐

Dimtype: DALI

Cutout dimension (mm): 72

Coversets




204 00 62 ANO COVERSET R 62 ANO

☐

204 00 62 B COVERSET R 62 B

☐

204 00 62 W COVERSET R 62 W

☐


204 00 90 ANO COVERSET R 90 ANO

☐

204 00 90 B COVERSET R 90 B

☐

204 00 90 W COVERSET R 90 W

☐


204 00 100 ANO COVERSET R 100 ANO

☐

204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐




204 62 62 ANO COVERSET S 62 ANO

☐


DELTALIGHT

INFORM R4 C DOWN 93048


26825 9320 FG-B

	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>328 10 01</u>	SUSPENSION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	
	<u>15225 0340 B</u>	SUSPENSION ST B	☐
		Cutout dimension (mm): 27	
	<u>15225 0340 W</u>	SUSPENSION ST W	☐


Electric connection parts

	<u>328 10 03</u>	CONNECTION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	

DELTALIGHT

INFORM R4 C DOWN 93048

26825 9320 FG-B



15225 0360 B CONNECTION ST B



Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W



Notes: