



BOXY XL R C 93020

REFERENCE



251 73 21 931 B-B

AVAILABLE IN

BLACK-BLACK 251 73 21 931 B-B

WHITE-BLACK 251 73 21 931 W-B

WHITE-WHITE 251 73 21 931 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0,75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,3W / CRI>90 (R9: 52) / 3000K / 2309lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	2309lm // 16,3W // 142lm/W
LED TECHNICS (LUMINAIRE)	2008lm // 18,7W // 107lm/W

Options

COVERSET R 90-100

SUSPENSION + CONNECTION TRIMLESS

Accessories

HONEYCOMB 78


SOFTENING LENS 78

GLASS SBL 78

For detailed installation instructions, please consult the manual : [251_73_21_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

☐

Coversets




204 00 90 ANO COVERSET R 90 ANO

☐

204 00 90 B COVERSET R 90 B

☐

204 00 90 W COVERSET R 90 W

☐

204 00 100 ANO COVERSET R 100 ANO

☐


204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐

Suspension parts



328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)


☐

DELTALIGHT

BOXY XL R C 93020

251 73 21 931 B-B

Light altering devices



Ø78

201 02 01 B HONEYCOMB 78 B

☐

Ø78

201 02 04 SOFTENING LENS 78

☐

Ø78

201 02 05 GLASS SBL 78

☐

Notes: