DELTALIGHT



OML50 - LED ARRAY DU TW 1968mm 950 DIM5

REFERENCE 31050 9005

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.5
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 44,6W / CRI>90 (R9: 50) / 2700K-5000K / 5856lm UP @ 2700K: LED cluster 22,3W / CRI>90 (R9: 50) / 2700K-5000K / 2928lm Or DOWN @ 5000K: LED cluster 40,5W / CRI>90 (R9: 50) / 2700K-5000K / 7008lm UP @ 5000K: LED cluster 20,3W / CRI>90 (R9: 50) / 2700K-5000K / 3504lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 5856lm // 44,6W // 131lm/W UP @ 2700K: 2928lm // 22,3W // 131lm/W Or DOWN @ 5000K: 7008lm // 40,5W // 173lm/W UP @ 5000K: 3504lm // 20,3W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes:

OML50 - LED ARRAY DU TW 1968mm 950 DIM5

31050 9005