

OML50 - LED ARRAY DU TW 1968mm 950 DIM5

31050 9005



 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.5
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 44,6W / CRI>90 (R9: 50) / 2700K-5000K / 5856lm UP @ 2700K: LED cluster 22,3W / CRI>90 (R9: 50) / 2700K-5000K / 2928lm Or DOWN @ 5000K: LED cluster 40,5W / CRI>90 (R9: 50) / 2700K-5000K / 7008lm UP @ 5000K: LED cluster 20,3W / CRI>90 (R9: 50) / 2700K-5000K / 3504lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 5856lm // 44,6W // 131lm/W UP @ 2700K: 2928lm // 22,3W // 131lm/W Or DOWN @ 5000K: 7008lm // 40,5W // 173lm/W UP @ 5000K: 3504lm // 20,3W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes:

DELTALIGHT

OML50 - LED ARRAY DU TW 1968mm 950 DIM5

31050 9005