
DELTALIGHT




FRAX M 927 LINEAR V

REFERENCE 26011 9230 N

AVAILABLE IN
ALU GREY 26011 9230 A
FLEMISH BRONZE OUTDOOR 26011 9230 FBRX
ANTHRACITE 26011 9230 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.4
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCL.LED POWER SUPPLY 900mA-DC INCL.LINEAR SPREAD LENS VERTICAL Oval spread 60°-15°

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 50) / 2700K / 2423lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	2423lm // 23,4W // 103lm/W
LED TECHNICS (LUMINAIRE)	1696lm // 27W // 63lm/W

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX M KAP

DELTALIGHT


FRAX M 927 LINEAR V

26011 9230 N

For detailed installation instructions, please consult the manual : **26011_XX30_HAND.pdf**


FINISH YOUR SPECIFICATION

Light altering devices



26070 0020 N FRAX M KAP N ☐

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS ☐

Notes: