
DELTALIGHT



OVIO 39 M20/M26H DALI 93035

REFERENCE 40114 9345 W-W

AVAILABLE IN
BLACK BRONZE-BLACK 40114 9345 BBR-B
WHITE BRONZE-WHITE 40114 9345 BBR-W
BRUSHED ANTHRACITE-BLACK 40114 9345 BRAT-B
BRUSHED ANTHRACITE-WHITE 40114 9345 BRAT-W
WHITE-BLACK 40114 9345 W-B
WHITE-WHITE 40114 9345 W-W



View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	35°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	780lm // 10W // 79lm/W

Accessories

HONEYCOMB 39
SOFTENING LENS 39
SANDBLASTED LENS 39
LINEAR SPREAD LENS 39


For detailed installation instructions, please consult the manual : **40114_XXX5_HAND.pdf**

OVIO 39 M20/M26H DALI 93035

40114 9345 W-W


FINISH YOUR SPECIFICATION

Profile




420 20 10 00 B SPM20 - PROFILE 1m B

Cutout dimension (mm): 57 x (L + 5)




420 20 20 00 B SPM20 - PROFILE 2m B

Cutout dimension (mm): 57 x (L + 5)




420 20 30 00 B SPM20 - PROFILE 3m B

Cutout dimension (mm): 57 x (L + 5)



23359 0010 B SLM26H - PROFILE 1m B

23359 0010 W SLM26H - PROFILE 1m W



23359 0020 B SLM26H - PROFILE 2m B

23359 0020 BRA SLM26H - PROFILE 2m BRA

23359 0020 BRAT SLM26H - PROFILE 2m BRAT

23359 0020 BRB SLM26H - PROFILE 2m BRB

23359 0020 BRBB SLM26H - PROFILE 2m BRBB

23359 0020 BRCU SLM26H - PROFILE 2m BRCU


23359 0020 BRG SLM26H - PROFILE 2m BRG

23359 0020 BROB SLM26H - PROFILE 2m BROB

DELTALIGHT

OVIO 39 M20/M26H DALI 93035

40114 9345 W-W

	23359 0020 PA	SLM26H - PROFILE 2m PA	☐
	23359 0020 W	SLM26H - PROFILE 2m W	☐
	**23359 0030 B**	SLM26H - PROFILE 3m B	☐
	23359 0030 BRA	SLM26H - PROFILE 3m BRA	☐
	23359 0030 BRAT	SLM26H - PROFILE 3m BRAT	☐
	23359 0030 BRB	SLM26H - PROFILE 3m BRB	☐
	23359 0030 BRBB	SLM26H - PROFILE 3m BRBB	☐
	23359 0030 BRCU	SLM26H - PROFILE 3m BRCU	☐
	23359 0030 BRG	SLM26H - PROFILE 3m BRG	☐
	23359 0030 BROB	SLM26H - PROFILE 3m BROB	☐
	23359 0030 PA	SLM26H - PROFILE 3m PA	☐
	23359 0030 W	SLM26H - PROFILE 3m W	☐
	**23397 0020 B**	SPM20 ST - PROFILE 2m B **Cutout dimension (mm): 32 x (L + 10)**	☐
	23397 0020 W	SPM20 ST - PROFILE 2m W	☐
	**23397 0030 B**	SPM20 ST - PROFILE 3m B **Cutout dimension (mm): 32 x (L + 10)**	☐
	23397 0030 W	SPM20 ST - PROFILE 3m W	☐

DELTALIGHT

OVIO 39 M20/M26H DALI 93035

40114 9345 W-W

Light altering devices

32210 0210 SOFTENING LENS 39 ☐

32210 0220 SANDBLASTED LENS 39 ☐

32210 0230 LINEAR SPREAD LENS 39 ☐



32210 0240 HONEYCOMB 39 ☐

Notes: