
DELTALIGHT




SUPERNOVA FLAT 95 DOWN-UP 930 DIM5

REFERENCE 20614 9305 W

AVAILABLE IN
NEGRO 20614 9305 B
BLANCO 20614 9305 W





View on website

General info	
LOCATION	interior
INSTALLATION	Techo Suspendido
INGRESS PROTECTION	IP20
WEIGHT (KG)	12.7
ADJUSTABILITY	no ajustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY 2800mA (DOWN) / 500mA (UP) 2 DALI ADDRESSES

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	con DALI
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2800mA: LED cluster 123,7W / CRI>90 (R9: 68) / 3000K / 16507lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm)
RVALUES	Rf: 89 / Rg: 97 Rf: 92 / Rg: 100
SDMC	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000 L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2800mA: 16507lm // 123,7W // 133lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2800mA: 12661lm // 142,3W // 89lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W

Requirements

SUSPENSION SET 25 DIM 3m
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
WIRELESS CONTROL DIM5

DELTALIGHT


SUPERNOVA FLAT 95 DOWN-UP 930 DIM5

20614 9305 W

For detailed installation instructions, please consult the manual : **20614_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION


Cable de alimentación



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐




203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Equipos de control diversos




300 90 004 ED5 WIRELESS CONTROL DIM5 ☐

Dimtype: WDL = Regulable inalámbrico

Cutout dimension (mm): 45

Plafones








204 00 62 ANO COVERSET R 62 ANO ☐

204 00 62 B COVERSET R 62 B ☐

DELTALIGHT

SUPERNOVA FLAT 95 DOWN-UP 930 DIM5

20614 9305 W

	204 00 62 W	COVERSET R 62 W	☐
	**204 00 90 ANO**	COVERSET R 90 ANO	☐
	204 00 90 B	COVERSET R 90 B	☐
	204 00 90 W	COVERSET R 90 W	☐
	**204 00 100 ANO**	COVERSET R 100 ANO	☐
	204 00 100 B	COVERSET R 100 B	☐
	204 00 100 W	COVERSET R 100 W	☐
	**204 62 62 ANO**	COVERSET S 62 ANO	☐
	204 62 62 B	COVERSET S 62 B	☐
	204 62 62 W	COVERSET S 62 W	☐
	**204 80 80 ANO**	COVERSET S 80 ANO	☐
	204 80 80 B	COVERSET S 80 B	☐
	204 80 80 W	COVERSET S 80 W	☐
	**204 90 90 ANO**	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐

SUPERNOVA FLAT 95 DOWN-UP 930 DIM5

20614 9305 W


204 90 90 W COVERSET S 90 W

Accesorios de Suspensión




274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W



328 25 43 ED SUSPENSION SET 25 DIM 3m



328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

Partes para conexión eléctrica



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: