DELTALIGHT





Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 360 DOWN-UP 94063 DIM5

REFERENCE 30735 9435 B-B

AVAILABLE IN
BLACK-BLACK 30735 9435 B-B
WHITE-BLACK 30735 9435 W-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver DALI DT6 : DOWN & UP on separate channels INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm² 1,6m

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 4000K / 7283lm UP (HO): LED cluster 60,5W / CRI>90 (R9: 50) / 4000K / 9104lm Or DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 4000K / 5286lm UP: LED cluster 41,8W / CRI>90 (R9: 50) / 4000K / 6736lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 7283lm // 48,4W // 151lm/W UP (HO): 9104lm // 60,5W // 151lm/W Or DOWN: 5286lm // 32,6W // 162lm/W UP: 6736lm // 41,8W // 161lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 5039lm // 55,7W // 91lm/W UP (HO): 5995lm // 69,6W // 86lm/W Or DOWN: 3657lm // 37,5W // 98lm/W UP: 4436lm // 48,1W // 92lm/W

Options

CABLE BASE R / S

DELTALIGHT


INFORM 40 SQ 360 DOWN-UP 94063 DIM5

30735 9435 B-B

For detailed installation instructions, please consult the manual : **30735_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Notes: