



Image may differ from the actual product
Consult drawing for correct size and structure



INFORM 40 SQ 360 DOWN-UP 94063 DIM5

30735 9435 B-B

BESCHIKBAAR IN

ZWART-ZWART 30735 9435 B-B

WIT-ZWART 30735 9435 W-B



Bekijk op website



Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Gependeld
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	5.9
RICHTBAARHEID	niet richtbaar
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver DALI DT6 : DOWN & UP on separate channels INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 4000K / 7283lm UP (HO): LED cluster 60,5W / CRI>90 (R9: 50) / 4000K / 9104lm Or DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 4000K / 5286lm UP: LED cluster 41,8W / CRI>90 (R9: 50) / 4000K / 6736lm
TM-30 WAARDEN	Rf: 90 / Rg: 101 DOWN: rf: 90 / Rg: 101 UP: rf: 90 / Rg: 101
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN (HO): 7283lm // 48,4W // 151lm/W UP (HO): 9104lm // 60,5W // 151lm/W Or DOWN: 5286lm // 32,6W // 162lm/W UP: 6736lm // 41,8W // 161lm/W
LED TECHNIEK (TOESTEL)	DOWN (HO): 5039lm // 55,7W // 91lm/W UP (HO): 5995lm // 69,6W // 86lm/W Or DOWN: 3657lm // 37,5W // 98lm/W UP: 4436lm // 48,1W // 92lm/W

DELTA LIGHT

INFORM 40 SQ 360 DOWN-UP 94063 DIM5

30735 9435 B-B


Opties

CABLE BASE R/S

Voor gedetailleerde montage gegevens, consulteer de handleiding : [30735_XXX5_HAND.pdf](#)

VERVOLLEDIG UW SPECIFICATIE

Stroomtoevoer

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Notes: