DELTALIGHT



OML50 - LED ARRAY DU TW 2296mm 950 DIM5

REFERENCE 31051 9005

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.8
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 52,1W / CRI>90 (R9: 50) / 2700K-5000K / 6832lm UP @ 2700K: LED cluster 26W / CRI>90 (R9: 50) / 2700K-5000K / 3416lm Or DOWN @ 5000K: LED cluster 47,3W / CRI>90 (R9: 50) / 2700K-5000K / 8176lm UP @ 5000K: LED cluster 23,6W / CRI>90 (R9: 50) / 2700K-5000K / 4088lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 6832lm // 52,1W // 131lm/W UP @ 2700K: 3416lm // 26W // 131lm/W Or DOWN @ 5000K: 8176lm // 47,3W // 173lm/W UP @ 5000K: 4088lm // 23,6W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes:

OML50 - LED ARRAY DU TW 2296mm 950 DIM5

31051 9005