
DELTALIGHT




# MINIGRID IN TRIMLESS 1 HP 92737

**REFERENCE** 100049 9220 B-B

AVAILABLE IN
**BLACK-BLACK** 100049 9220 B-B
**BLACK-WHITE** 100049 9220 B-W
**WHITE-BLACK** 100049 9220 W-B
**WHITE-WHITE** 100049 9220 W-W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | rectangle - KIT |
| **RECESSED DEPTH (MM)** | 160 |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.6 |
| **ADJUSTABILITY** | 0° to 25° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-37°<br>EXCL.LED POWER SUPPLY 500-700mA-DC |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 16,3-23,2W / CRI>90 (R9: 60) / 2700K / 2209-3031lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 37° |
| **LED TECHNICS (LIGHT SOURCE)** | 3031lm // 23,2W // 130lm/W |
| **LED TECHNICS (LUMINAIRE)** | 2164lm // 26,7W // 81lm/W |

**Requirements**

MINIGRID IN 1 MOUNTING KIT HP
LED POWER SUPPLY 500 / 700mA-DC DIM (Remote)

**Accessories**

HONEYCOMB 72
SOFTENING LENS 72

For detailed installation instructions, please consult the manual : **100049_XXX0_HAND.pdf**

DELTALIGHT

# MINIGRID IN TRIMLESS 1 HP 92737

100049 9220 B-B

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit | |
|---|---|---|
|  **System ceiling** | 202 71 95 01 HP - MINIGRID IN 1 MOUNTING KIT HP | Required |
|  **Plasterboard** | 202 71 95 01 HP - MINIGRID IN 1 MOUNTING KIT HP | Required |
|  **Stucanet** | 202 71 95 01 HP - MINIGRID IN 1 MOUNTING KIT HP | Required |


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures

**Min current | Max current**


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 1

**Dimtype: 1-10V**


**Cutout dimension (mm): 30**




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 1

**Dimtype: DALI**


**Cutout dimension (mm): 45**




**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 1

**Dimtype: non-dimmable**


**Cutout dimension (mm): 30**




**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 1

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 45**




**300 48 700 ED1** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 — 1


**Dimtype: 1-10V**

**Cutout dimension (mm): 30**

DELTALIGHT

# MINIGRID IN TRIMLESS 1 HP 92737


100049 9220 B-B




**300 48 700 ED5** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 — 1

**Dimtype: DALI**


**Cutout dimension (mm): 45**




**300 48 700 MDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL — 1

**Dimtype: non-dimmable**


**Cutout dimension (mm): 30**




**300 48 700 WDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL — 1

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 45**




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6 — 1 | 1

**Dimtype: mains (phase cut-off) or push button**


**Cutout dimension (mm): 56**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9 — 2(2) | 2(1)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 82**




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7 — 1(0) | 1(0)


**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 72**




**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — - | 1


**Dimtype: 1-10V or DALI or push button**




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5 — 1(0) | 1(0)

**Dimtype: DALI**


**Cutout dimension (mm): 72**




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9 — 3(2) | 2(1)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**





**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7 — 1(0) | 0

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**

# MINIGRID IN TRIMLESS 1 HP 92737


100049 9220 B-B




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5 1(0) | 0

**Dimtype: DALI**


**Cutout dimension (mm): 55**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV 2->2 | 2

**Dimtype: non-dimmable**


**Cutout dimension (mm): 90**




**21012 0010** LED POWER SUPPLY MULTI POWER 1 | 1

**Dimtype: non-dimmable**


**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1 1 | 1

**Dimtype: 1-10V**


**Cutout dimension (mm): 54**




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5 1 | 1

**Dimtype: DALI**


**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL 2(2) | 2(1)

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL 1 | 1

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 54**




**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 0 | 1

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 1 | 0

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21012 0490** LED POWER SUPPLY 700mA-DC / 30W IP68 1(0)


**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**

DELTALIGHT

# MINIGRID IN TRIMLESS 1 HP 92737


100049 9220 B-B




**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68 1(0)

**Dimtype: non-dimmable**


**Cutout dimension (mm): 60**




**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 1

**Dimtype: DALI**

**Cutout dimension (mm): 30**





**21032 0315** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 1

**Dimtype: DALI**

**Cutout dimension (mm): 30**


## Mounting kits




**202 71 95 01 HP** MINIGRID IN 1 MOUNTING KIT HP

**Cutout dimension (mm): 130 x 130**

## Light altering devices




**201 05 01 B** HONEYCOMB 72 B




**201 05 04** SOFTENING LENS 72

Notes: