

OML50 - LED ARRAY DU TW 2624mm 950 DIM5

31052 9005



 [View on website](#)



General info

| | |
|---------------------------|---|
| LOCATION | indoor |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 3.1 |
| INFORMATION | INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT |

Electrical info

| | |
|---------------------|----------------------|
| ELECTRICAL | 220-240V / 0 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | DALI |
| ENERGY CLASS | E |
| CERTIFICATES | EPD, RCM |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | DOWN @ 2700K: LED cluster 59,5W / CRI>90 (R9: 50) / 2700K-5000K / 7808lm UP @ 2700K: LED cluster 29,8W / CRI>90 (R9: 50) / 2700K-5000K / 3904lm Or DOWN @ 5000K: LED cluster 54W / CRI>90 (R9: 50) / 2700K-5000K / 9344lm UP @ 5000K: LED cluster 27W / CRI>90 (R9: 50) / 2700K-5000K / 4672lm |
| SDCM | SDCM3 |
| RISKGROUP | RG1 |
| LED TECHNICS (LIGHT SOURCE) | DOWN @ 2700K: 7808lm // 59,5W // 131lm/W UP @ 2700K: 3904lm // 29,8W // 131lm/W Or DOWN @ 5000K: 9344lm // 54W // 173lm/W UP @ 5000K: 4672lm // 27W // 173lm/W |

Options

WIRELESS CONTROL DIM5

Notes:

DELTALIGHT

OML50 - LED ARRAY DU TW 2624mm 950 DIM5

31052 9005