
DELTALIGHT




OBLIX 70 930

REFERENCE 220 77 811 930 A

AVAILABLE IN
ALU GREY 220 77 811 930 A
ANTHRACITE 220 77 811 930 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	3.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	573lm // 6,7W // 86lm/W

Options

PLATE 7
PIN 12
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : **220_77_811_XXX_HAND.pdf**


DELTALIGHT

OBLIX 70 930

220 77 811 930 A

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142

☐



216 12 01 IP68 CONNECTION KIT


☐



216 12 02 IP68 CONNECTOR 3P


☐

Pins and plates for bollards



229 01 12 PIN 12

☐



229 02 07 PLATE 7

☐

Notes: