



D-LINER 19 INF LOC1 1114 93058 RD

32017 9320 B

AVAILABLE IN
BLACK 32017 9320 B



 [View on website](#)



General info

| | |
|---------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Ceiling Recessed |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | 48 x REFLECTOR 58° EXCL.LED POWER SUPPLY 520mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male green |

Electrical info

| | |
|---------------------|-----|
| CLASS | III |
| ENERGY CLASS | C |

Lightsource info

| | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED cluster 17,3W / CRI>90 / 3000K / 3058lm |
| BEAMANGLE | 58° |
| LED TECHNICS (LIGHT SOURCE) | 3058lm // 17,3W // 177lm/W |
| LED TECHNICS (LUMINAIRE) | 2602lm // 19,9W // 131lm/W |

Requirements

LED POWER SUPPLY SET LOC PARALLEL

Options

CONNECTING CABLE LOC PARALLEL

For detailed installation instructions, please consult the manual : [32017_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type

Mounting Kit



Acoustic climate-control ceiling Interalu SAPP

-

DELTALIGHT

D-LINER 19 INF LOC1 1114 93058 RD

32017 9320 B



Acoustic climate-control ceiling Hunter Douglas 30BD

FINISH YOUR SPECIFICATION


Emergency units

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5

1

Dimtype: DALI

Current supply



32010 1200 T CONNECTOR LOC PARALLEL



32010 1310 CONNECTING CABLE LOC PARALLEL 1m



32010 1320 CONNECTING CABLE LOC PARALLEL 2m



32010 1330 CONNECTING CABLE LOC PARALLEL 3m



32010 1340 CONNECTING CABLE LOC PARALLEL 4m

DELTALIGHT

D-LINER 19 INF LOC1 1114 93058 RD

32017 9320 B



32010 1350 CONNECTING CABLE LOC PARALLEL 5m


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



32010 0105 LED POWER SUPPLY SET LOC PARALLEL 520mA / 35W DIM5

1


Dimtype: DALI



32010 0145 LED POWER SUPPLY SET LOC PARALLEL 1040mA / 35W DIM5

2->2


Dimtype: DALI



32010 0425 LED POWER SUPPLY SET LOC PARALLEL 1560mA / 100W DIM5

3->3

Dimtype: DALI



32010 0455 LED POWER SUPPLY SET LOC PARALLEL 2080mA / 100W DIM5

4->4

Dimtype: DALI

Notes: