

INFORM SQ F144-5 94067

25524 9420 W-B


AVAILABLE IN

BLACK-BLACK 25524 9420 B-B

BLACK-FLEMISH GOLD 25524 9420 B-FG

WHITE-BLACK 25524 9420 W-B

WHITE-WHITE 25524 9420 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 500/750mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,6-27,9W / CRI>90 (R9: 50) / 4000K / 2784-4026lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	4026lm // 27,9W // 144lm/W
LED TECHNICS (LUMINAIRE)	3515lm // 32,1W // 110lm/W

Requirements

INFORM POWER SUPPLY 45W

For detailed installation instructions, please consult the manual : [25524_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
360 121 30	25510 0070 INFORM POWER SUPPLY 50W Dimtype: non-dimmable	1
70 215 131	25510 0385 INFORM POWER SUPPLY 45W DIM5 Dimtype: DALI	1
70 215 131	25510 0430 INFORM POWER SUPPLY 45W Dimtype: non-dimmable	1

Notes: