





SPY 90 ON 92745 DIM1

19882 9231 W

AVAILABLE IN
BLACK 19882 9231 B
FULL WHITE 19882 9231 FW
WHITE 19882 9231 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC Optional REFLECTORS 18° & 30° available

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 23,2W / CRI>90 (R9: 60) / 2700K / 303lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	303lm // 23,2W // 130lm/W
LED TECHNICS (LUMINAIRE)	2144lm // 26,7W // 80lm/W

Requirements

SPY 90 TUBE

Accessories

HONEYCOMB 75
SPREAD LENS 75
LINEAR SPREAD LENS 75
SOFTENING LENS 75
GLASS SBL 75

DELTALIGHT


SPY 90 ON 92745 DIM1

19882 9231 W

For detailed installation instructions, please consult the manual : [19882_XXX1_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices




¹³ **19810 0110 B** HONEYCOMB 75 SINGLE USE B

☐




¹⁴ **19810 0120 B** HONEYCOMB 75 DOUBLE USE B

☐




¹³ **19810 0130** GLASS SBL 75

☐




¹³ **19810 0140** LINEAR SPREAD LENS 75

☐



¹³ **19810 0150** SOFTENING LENS 75

☐



¹³ **19810 0160** SPREAD LENS 75

☐

Finish your product



²⁸ **19810 0170 B** SPY 90 TUBE B

☐

DELTALIGHT

SPY 90 ON 92745 DIM1

19882 9231 W

<u>19810 0170 CR</u>	SPY 90 TUBE CR	☐
<u>19810 0170 DC</u>	SPY 90 TUBE DC	☐
<u>19810 0170 FBR</u>	SPY 90 TUBE FBR	☐
<u>19810 0170 FG</u>	SPY 90 TUBE FG	☐
<u>19810 0170 GC</u>	SPY 90 TUBE GC	☐
<u>19810 0170 PB</u>	SPY 90 TUBE PB	☐
<u>19810 0170 W</u>	SPY 90 TUBE W	☐

Replaceable reflector / lens

	<u>19810 0200</u>	SPY 90 REFLECTOR 18°	☐
	<u>19810 0210</u>	SPY 90 REFLECTOR 30°	☐
	<u>19810 0220</u>	SPY 90 REFLECTOR 45°	☐

Notes: