



M26L - SPY 391 92720 MDL

23258 9220 B

AVAILABLE IN

BLACK 23258 9220 B

BRUSHED ALU 23258 9220 BRA

BRUSHED ANTHRACITE 23258 9220 BRAT

BRUSHED COPPER 23258 9220 BRCU

BRUSHED GOLD 23258 9220 BRG

BRUSHED OLD BRONZE 23258 9220 BROB



FLEMISH BRONZE 23258 9220 FBR

FLEMISH GOLD 23258 9220 FG

GOLD COLOURED 23258 9220 GC

PIANO BLACK 23258 9220 PB

WHITE 23258 9220 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	849lm // 9,9W // 86lm/W

Remarks
[Take a look at our MAGNETIC PROFILES movie](#)

Requirements
 SPY 39 TUBE or VISOR 39
 LED POWER SUPPLY 48V-DC

Options
 DIMMABLE MODULATOR

DELTALIGHT

M26L - SPY 391 92720 MDL


23258 9220 B

For detailed installation instructions, please consult the manual : [23258_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




21032 0030 SMART 48 MODULATOR PLUG-IN WD

19

Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button




300 90 012 SMART 48 MODULATOR WD

19


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN


10

Dimtype: non-dimmable

DELTALIGHT

M26L - SPY 391 92720 MDL


23258 9220 B



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



24144 0030 B VISOR 39 B

Finish your product



24144 0010 B SPY 39 TUBE B

24144 0010 FBR SPY 39 TUBE FBR

24144 0010 FC SPY 39 TUBE FC

24144 0010 GC SPY 39 TUBE GC

24144 0010 W SPY 39 TUBE W



24144 0070 SPY 39 TUBE SBL

DELTALIGHT


M26L - SPY 391 92720 MDL

23258 9220 B


COMPATIBLE COMPOSABLES

SHIFTLINE M26L FLOOR

Available Colours



29321 0010 SLM26L F MDL




29322 002W SLM26L F MDL WD




SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile


Available Colours



23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m




23375 0020 SLM35R - PROFILE 2m



DELTALIGHT

M26L - SPY 391 92720 MDL

23258 9220 B



23375 0030 SLM35R - PROFILE 3m



Notes: