
DELTALIGHT




# M52 - SPY 52 92720 DIM5

**REFERENCE** 24435 9225 W

AVAILABLE IN
**BLACK** 24435 9225 B
**FLEMISH BRONZE** 24435 9225 FBR
**FLEMISH GOLD** 24435 9225 FG
**GOLD COLOURED** 24435 9225 GC
**WHITE** 24435 9225 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-20°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 30° & 45° available |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 12,4W / CRI>90 (R9: 60) / 2700K / 1403lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 20° |
| **LED TECHNICS (LIGHT SOURCE)** | 1403lm // 12,4W // 113lm/W |
| **LED TECHNICS (LUMINAIRE)** | 879lm // 14,3W // 62lm/W |

**Remarks**

**Take a look at our MAGNETIC PROFILES movie**

**Requirements**

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

**Accessories**

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

DELTALIGHT

# M52 - SPY 52 92720 DIM5

24435 9225 W

For detailed installation instructions, please consult the manual : **24435_XXX5_HAND.pdf**


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

**Min current | Max current**





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 7

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 16


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 7

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 14


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

### Light altering devices




**19810 0010 B** HONEYCOMB 42 SINGLE USE B





**19810 0020** LINEAR SPREAD LENS 42

DELTALIGHT

# M52 - SPY 52 92720 DIM5


24435 9225 W





**19810 0030** SPREAD LENS 42




**19810 0040** SOFTENING LENS 42





**19810 0050** GLASS SBL 42




**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

## Finish your product




**19810 0100 B** SPY 52 TUBE B


**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG

**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W

## Replaceable reflector / lens





**19810 0180** SPY 52 REFLECTOR 20°

# M52 - SPY 52 92720 DIM5

24435 9225 W




**19810 0190** SPY 52 REFLECTOR 45°




**19810 0240** SPY 52 REFLECTOR 30°

## COMPATIBLE COMPOSABLES

| SPLITLINE M52 profile | Available Colours |
|---|---|
| **420 52 10 00** SPM52 - PROFILE 1m | |
| **420 52 20 00** SPM52 - PROFILE 2m | |
| **420 52 30 00** SPM52 - PROFILE 3m | |
| **24413 0000** SPM52 - PROFILE | |

Notes: