



## M26L - SPY 391 93040 DIM5

23259 9335 BRCU

AVAILABLE IN

**BLACK** 23259 9335 B

**BRUSHED ALU** 23259 9335 BRA

**BRUSHED ANTHRACITE** 23259 9335 BRAT

**BRUSHED COPPER** 23259 9335 BRCU

**BRUSHED GOLD** 23259 9335 BRG

**BRUSHED OLD BRONZE** 23259 9335 BROB



**FLEMISH BRONZE** 23259 9335 FBR

**FLEMISH GOLD** 23259 9335 FG

**GOLD COLOURED** 23259 9335 GC

**PIANO BLACK** 23259 9335 PB

**WHITE** 23259 9335 W



[View on website](#)



### General info

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| <b>LOCATION</b>           | indoor                                            |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted    |
| <b>INGRESS PROTECTION</b> | IP20                                              |
| <b>WEIGHT (KG)</b>        | 0.3                                               |
| <b>ADJUSTABILITY</b>      | 0° to 85° swiveling, 360° rotatable               |
| <b>INFORMATION</b>        | REFLECTOR WFL-40°<br>EXCL.LED POWER SUPPLY 48V-DC |

### Electrical info

|                     |               |
|---------------------|---------------|
| <b>ELECTRICAL</b>   | 48V-DC        |
| <b>CLASS</b>        | III           |
| <b>DIM TYPE</b>     | DALI          |
| <b>ENERGY CLASS</b> | D             |
| <b>CERTIFICATES</b> | CB, ENEC, EPD |

### Lightsource info

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm |
| <b>TM-30 VALUES</b>                | rf: 90 / Rg: 99                                   |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>BEAMANGLE</b>                   | 40°                                               |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1089lm // 8,6W // 127lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 883lm // 9,9W // 89lm/W                           |

### Remarks

Take a look at our [MAGNETIC PROFILES](#) movie

### Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC






# DELTALIGHT

## M26L - SPY 391 93040 DIM5

23259 9335 BRCU

For detailed installation instructions, please consult the manual : [23259\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


| LED power supplies                                                                                                                                                                                                                                                                                                                                                         |    | # of Fixtures             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------------------|
| <div><div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |    | Min current   Max current |
| <div><div></div><div><b>300 89 48 100</b> LED POWER SUPPLY 48V-DC / 100W DIN<br/>Dimtype: non-dimmable</div></div>                                                                                                                                                                         | 10 | <input type="text"/>      |
| <div><div></div><div><b>300 89 48 240</b> LED POWER SUPPLY 48V-DC / 240W DIN<br/>Dimtype: non-dimmable</div></div>                                                                                                                                                                        | 24 | <input type="text"/>      |
| <div><div></div><div><b>21012 0230</b> LED POWER SUPPLY 48V-DC / 100W<br/>Dimtype: non-dimmable<br/>Cutout dimension (mm): 40</div></div>                                                                                                                                                | 10 | <input type="text"/>      |
| <div><div></div><div><b>21012 0240</b> LED POWER SUPPLY 48V-DC / 200W<br/>Dimtype: non-dimmable<br/>Cutout dimension (mm): 40</div></div>                                                                                                                                                | 20 | <input type="text"/>      |
| Light altering devices                                                                                                                                                                                                                                                                                                                                                     |    |                           |
| <div><div></div><div><b>24144 0030 B</b> VISOR 39 B</div></div>                                                                                                                                                                                                                          |    | <input type="text"/>      |

# DELTALIGHT

## M26L - SPY 391 93040 DIM5

23259 9335 BRCU

### Finish your product



**24144 0010 B** SPY 39 TUBE B

☐

**24144 0010 FBR** SPY 39 TUBE FBR

☐

**24144 0010 FG** SPY 39 TUBE FG

☐

**24144 0010 GC** SPY 39 TUBE GC

☐

**24144 0010 W** SPY 39 TUBE W

☐


**24144 0070** SPY 39 TUBE SBL

☐


## COMPATIBLE COMPOSABLES

### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


### Available Colours




**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m







**23358 0030** SLM26L - PROFILE 3m



# DELTALIGHT

## M26L - SPY 391 93040 DIM5

23259 9335 BRCU

| SHIFTLINE M35R profile                                                             |                                       | Available Colours                                                                   |
|------------------------------------------------------------------------------------|---------------------------------------|-------------------------------------------------------------------------------------|
|   | <b>23375 0000</b> SLM35R - PROFILE    |  |
|   | <b>23375 0010</b> SLM35R - PROFILE 1m |  |
|   | <b>23375 0020</b> SLM35R - PROFILE 2m |  |
|  | <b>23375 0030</b> SLM35R - PROFILE 3m |  |

Notes: