
DELTALIGHT





# SUPERLOOP HC 200 SBL 930

**REFERENCE** 20549 9300 FBR

AVAILABLE IN
**BLACK** 20549 9300 B
**FLEMISH BRONZE** 20549 9300 FBR
**FLEMISH GOLD** 20549 9300 FG
**WHITE** 20549 9300 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Suspended |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 6.5 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | INCL.PC SBL<br>2 SEGMENTS<br>EXCL.LED POWER SUPPLY 24-DC<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m<br>INCL.2 x CABLE 2 x 0.75mm² |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 24V-DC |
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | 2 x (LED FLEX FP 45W / CRI>90 / 3000K / 5445lm) |
| **LED TECHNICS (LIGHT SOURCE)** | 10890 lm // 90 W // 121 lm/W |
| **LED TECHNICS (LUMINAIRE)** | 4900lm // 103,5W // 47lm/W |

**Requirements**

LED POWER SUPPLY 24V-DC

**Options**

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : **20549_XXX0_HAND.pdf**


DELTALIGHT

# SUPERLOOP HC 200 SBL 930

20549 9300 FBR

## FINISH YOUR SPECIFICATION

### Current supply




**203 99 55 ANO** CABLE BASE R ANO ☐

**203 99 55 B** CABLE BASE R B ☐

**203 99 55 W** CABLE BASE R W ☐




**203 99 56 ANO** CABLE BASE S ANO ☐

**203 99 56 B** CABLE BASE S B ☐


**203 99 56 W** CABLE BASE S W ☐

### LED power supplies

### # of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**300 89 24 80 ED1** LED POWER SUPPLY 24V-DC / 80W DIM1 1/2 ☐

**Dimtype: 1-10V**


**Cutout dimension (mm): 75**




**300 89 24 150** LED POWER SUPPLY 24V-DC / 150W 1 ☐

**Dimtype: non-dimmable**

**Cutout dimension (mm): 75**





**300 89 24 480** LED POWER SUPPLY 24V-DC / 480W DIN 3 ☐

**Dimtype: non-dimmable**

# SUPERLOOP HC 200 SBL 930


20549 9300 FBR




**300 90 003 ED1** 24V-DC / 4A DIM1 UNIT 1/2

**Dimtype: 1-10V**


**Cutout dimension (mm): 30**




**300 90 003 ED5** 24V-DC / 4A DIM5 UNIT 1/2


**Dimtype: DALI**

**Cutout dimension (mm): 30**




**300 90 010** 24V-DC / 2 x 4A WIRELESS DIM UNIT 1/2


**Dimtype: WDL = wireless dimmable**




**21012 0111** LED POWER SUPPLY 24V-DC / 90W IP67 DIM1 1/2

**Dimtype: 1-10V**


**Cutout dimension (mm): 75**




**21012 0121** LED POWER SUPPLY 24V-DC / 120W IP67 DIM1 1/2

**Dimtype: 1-10V**


**Cutout dimension (mm): 75**




**21012 0145** LED POWER SUPPLY 24V-DC / 90W IP67 DIM5 1/2

**Dimtype: DALI**


**Cutout dimension (mm): 75**




**21012 0155** LED POWER SUPPLY 24V-DC / 120W IP67 DIM5 1/2

**Dimtype: DALI**


**Cutout dimension (mm): 75**




**21012 0181** LED POWER SUPPLY 24V-DC / 90W DIM1 1/2

**Dimtype: 1-10V**


**Cutout dimension (mm): 70**




**21012 0191** LED POWER SUPPLY 24V-DC / 120W DIM1 1/2

**Dimtype: 1-10V**

**Cutout dimension (mm): 70**




**21012 0225** LED POWER SUPPLY 24V-DC / 100W DIM5 1/2

**Dimtype: DALI**

**Cutout dimension (mm): 70**

DELTALIGHT

# SUPERLOOP HC 200 SBL 930


20549 9300 FBR

## Miscellaneous control equipment

## # of Fixtures

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**300 90 24 ED2** LED DIMMODULE 24V / 3CH / 6A DIM2 — 1

**Dimtype: DALI or push button**


## Coversets




**204 00 62 ANO** COVERSET R 62 ANO

**204 00 62 B** COVERSET R 62 B


**204 00 62 W** COVERSET R 62 W




**204 00 90 ANO** COVERSET R 90 ANO

**204 00 90 B** COVERSET R 90 B


**204 00 90 W** COVERSET R 90 W




**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B



**204 00 100 W** COVERSET R 100 W






**204 62 62 ANO** COVERSET S 62 ANO

# SUPERLOOP HC 200 SBL 930


20549 9300 FBR

| | | |
|---|---|---|
| | **204 62 62 B** | COVERSET S 62 B |
| | **204 62 62 W** | COVERSET S 62 W |
|  | **204 80 80 ANO** | COVERSET S 80 ANO |
| | **204 80 80 B** | COVERSET S 80 B |
| | **204 80 80 W** | COVERSET S 80 W |
|  | **204 90 90 ANO** | COVERSET S 90 ANO |
| | **204 90 90 B** | COVERSET S 90 B |
| | **204 90 90 W** | COVERSET S 90 W |

## Suspension parts

| | | |
|---|---|---|
|  | **328 10 01** | SUSPENSION TRIMLESS O.F.A. |
| | | **Cutout dimension (mm): 62 (CONCRETE: 102)** |
|  | **15225 0340 B** | SUSPENSION ST B |
| | | **Cutout dimension (mm): 27** |
| | **15225 0340 W** | SUSPENSION ST W |

## Electric connection parts

| | | |
|---|---|---|
|  | **328 10 03** | CONNECTION TRIMLESS O.F.A. |
| | | **Cutout dimension (mm): 62 (CONCRETE: 102)** |

DELTALIGHT

# SUPERLOOP HC 200 SBL 930

20549 9300 FBR




**15225 0360 B** CONNECTION ST B

**Cutout dimension (mm): 43**

**15225 0360 W** CONNECTION ST W

Notes: