
DELTALIGHT




M26L - MULTINOVA 30 TW 930 DIM5

REFERENCE 27944 9005 W

AVAILABLE IN
BLACK 27944 9005 B
GOLD COLOURED 27944 9005 GC
WHITE 27944 9005 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,4W / CRI>90 (R9: 63) / 2700K-6500K / 1338lm
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	1338lm // 9,4W // 142lm/W
LED TECHNICS (LUMINAIRE)	993lm // 10,8W // 92lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **27944_XXX5_HAND.pdf**

DELTALIGHT

M26L - MULTINOVA 30 TW 930 DIM5

27944 9005 W


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 9

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 22


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 9

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 18


Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours



23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m




23358 0020 SLM26L - PROFILE 2m

DELTALIGHT

M26L - MULTINOVA 30 TW 930 DIM5


27944 9005 W




23358 0030 SLM26L - PROFILE 3m

SHIFTLINE M35R profile


Available Colours




23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m

Notes: