



EXCLUSIVELY AVAILABLE IN INDIA

COMPO S IP44 93020

9 15743 9320 B


AVAILABLE IN

NOIR 9 15743 9320 B

CHROME 9 15743 9320 C

CHROME FONCÉ 9 15743 9320 DC

BLANC 9 15743 9320 W



 [View on website](#)



General info

LOCATION	interieur-exterieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.136
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 3000K / 495lm
SDMC	SDCM2
RISKGROUP	RG1
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	495lm // 6,4W // 120lm/W
LED TECHNICS (LUMINAIRE)	393lm // 7,4W // 53lm/W

Requirements

LED POWER SUPPLY 350 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B
COMPO S LINEAR SPREAD LENS
COMPO S SPREAD LENS
COMPO S SOFTENING LENS
COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9_15743_XXX0_HAND.pdf](#)

DELTALIGHT

COMPO S IP44 93020

9 15743 9320 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 3100 LED POWER SUPPLY 18W NO DIM 1400mA	1->4 ☐
15710 3300 LED POWER SUPPLY MULTIPOWER 15W NO DIM 350mA	1->2 ☐
15710 3800 LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA	1 ☐
15710 4500 LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA	1 ☐
15710 5000 LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13 ☐
Dimtype: DALI	
15710 5300 LED POWER SUPPLY MULTIPOWER 12W DALI DT6 350mA	1 ☐
Dimtype: DALI	

kit de montage

	15710 0010 B MOUNTING KIT COMPO S TRIM B	☐
	Cutout dimension (mm): 55	
	15710 0010 W MOUNTING KIT COMPO S TRIM W	☐

COMPO S IP44 93020

9 15743 9320 B



15710 0040 MOUNTING KIT COMPO S TRIMLESS

☐

Cutout dimension (mm): 55

modifier les dispositifs de lumière

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

☐

15710 0110 COMPO S LINEAR SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

☐

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

☐

Cutout dimension (mm): 26,5

Notes: