



## M26L - BOXY R 92733 DIM5

10731 9225 W-W



AVAILABLE IN

**BLACK-BLACK** 10731 9225 B-B

**BLACK-FLEMISH BRONZE** 10731 9225 B-FBR

**BLACK-FLEMISH GOLD** 10731 9225 B-FG

**WHITE-WHITE** 10731 9225 W-W



[View on website](#)



| General info       |                                                  |
|--------------------|--------------------------------------------------|
| LOCATION           | indoor                                           |
| INSTALLATION       | Low voltage systems Low voltage system mounted   |
| INGRESS PROTECTION | IP20                                             |
| WEIGHT (KG)        | 0.4                                              |
| ADJUSTABILITY      | non adjustable                                   |
| INFORMATION        | REFLECTOR FL-33°<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info |          |
|-----------------|----------|
| ELECTRICAL      | 48V-DC   |
| CLASS           | III      |
| DIM TYPE        | DALI     |
| ENERGY CLASS    | E        |
| CERTIFICATES    | CB, ENEC |

| Lightsource info            |                                                   |
|-----------------------------|---------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                               |
| LIGHTSOURCE                 | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| TM-30 VALUES                | rf: 89 / Rg: 100                                  |
| SDCM                        | SDCM1                                             |
| RISKGROUP                   | RG1                                               |
| LM80                        | L90B10 > 50000                                    |
| BEAMANGLE                   | 33°                                               |
| LED TECHNICS (LIGHT SOURCE) | 1041lm // 8,6W // 121lm/W                         |
| LED TECHNICS (LUMINAIRE)    | 815lm // 9,9W // 82lm/W                           |

| Remarks                                                    |  |
|------------------------------------------------------------|--|
| Take a look at our <a href="#">MAGNETIC PROFILES movie</a> |  |

| Requirements            |  |
|-------------------------|--|
| LED POWER SUPPLY 48V-DC |  |

| Accessories         |  |
|---------------------|--|
| BOXY HONEYCOMB      |  |
| BOXY SOFTENING LENS |  |
| BOXY GLASS SBL      |  |

# DELTALIGHT

## M26L - BOXY R 92733 DIM5

10731 9225 W-W

For detailed installation instructions, please consult the manual : [10731\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices



Ø40



Ø45

**251 70 03 01 B** BOXY HONEYCOMB B

**251 70 03 01 W** BOXY HONEYCOMB W



Ø40




Ø45

**251 70 03 04 B** BOXY SOFTENING LENS B





# DELTALIGHT

## M26L - BOXY R 92733 DIM5

10731 9225 W-W

|                                                                                   |                                             |                          |
|-----------------------------------------------------------------------------------|---------------------------------------------|--------------------------|
|                                                                                   | <b>251 70 03 04 W</b> BOXY SOFTENING LENS W | <input type="checkbox"/> |
|  | <b>251 70 03 05 B</b> BOXY GLASS SBL B      | <input type="checkbox"/> |
|                                                                                   | <b>251 70 03 05 W</b> BOXY GLASS SBL W      | <input type="checkbox"/> |

### COMPATIBLE COMPOSABLES

| SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)                                                                          | Available Colours                                                                     |
|---------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  <b>23358 0000</b> SLM26L - PROFILE      |    |
|  <b>23358 0010</b> SLM26L - PROFILE 1m |  |
|  <b>23358 0020</b> SLM26L - PROFILE 2m |  |
|  <b>23358 0030</b> SLM26L - PROFILE 3m |  |

Notes: