



M20/M26H - SPY 52 SOFT 93020 DIM5

23399 9025 FG

AVAILABLE IN



BLACK 23399 9025 B

FLEMISH BRONZE 23399 9025 FBR

FLEMISH GOLD 23399 9025 FG

GOLD COLOURED 23399 9025 GC

WHITE 23399 9025 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCLLED POWER SUPPLY 48V-DC Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	650lm // 11,7W // 55lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 52 TUBE

LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42

SOFTENING LENS 42

DELTALIGHT

M20/M26H - SPY 52 SOFT 93020 DIM5

23399 9025 FG

GLASS SBL 42

For detailed installation instructions, please consult the manual : [23399_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

8


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

8

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W

17


Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



19810 0010 B HONEYCOMB 42 SINGLE USE B



19810 0020 LINEAR SPREAD LENS 42

DELTALIGHT

M20/M26H - SPY 52 SOFT 93020 DIM5

23399 9025 FG

	19810 0030	SPREAD LENS 42	☐
	19810 0040	SOFTENING LENS 42	☐
	19810 0050	GLASS SBL 42	☐
	19810 0060 B	HONEYCOMB 42 DOUBLE USE B	☐

Finish your product

	19810 0100 B	SPY 52 TUBE B	☐
	19810 0100 FBR	SPY 52 TUBE FBR	☐
	19810 0100 FG	SPY 52 TUBE FG	☐
	19810 0100 GC	SPY 52 TUBE GC	☐
	19810 0100 W	SPY 52 TUBE W	☐

Replaceable reflector / lens

	19810 0180	SPY 52 REFLECTOR 20°	☐
--	-------------------	----------------------	--------------------------

DELTALIGHT

M20/M26H - SPY 52 SOFT 93020 DIM5

23399 9025 FG



19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°



COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL		Available Colours
	30411 9205 SHIFTLINE M26H + SBL 2m DIM5	
	30411 9305 SHIFTLINE M26H + SBL 2m DIM5	
	30412 9205 SHIFTLINE M26H + SBL 3m DIM5	
	30412 9305 SHIFTLINE M26H + SBL 3m DIM5	
	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	

DELTALIGHT

M20/M26H - SPY 52 SOFT 93020 DIM5

23399 9025 FG

SHIFTLINE M26H profile		Available Colours
	23359 0000 SLM26H - PROFILE	
	23359 0010 SLM26H - PROFILE 1m	
	23359 0020 SLM26H - PROFILE 2m	
	23359 0030 SLM26H - PROFILE 3m	


SPLITLINE M20 ST profile		Available Colours
	23397 0000 SPM20 ST - PROFILE	
	23397 0020 SPM20 ST - PROFILE 2m	
	23397 0030 SPM20 ST - PROFILE 3m	

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	


DELTALIGHT

M20/M26H - SPY 52 SOFT 93020 DIM5

23399 9025 FG



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: