



COMPO L 92710

9 15735 9210 B

AVAILABLE IN  
**BLACK** 9 15735 9210 B  
**CHROMED** 9 15735 9210 C  
**DARK CHROMED** 9 15735 9210 DC  
**WHITE** 9 15735 9210 W



EXCLUSIVELY AVAILABLE IN INDIA



[View on website](#)



| General info                       |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| LOCATION                           | indoor                                                                       |
| INSTALLATION                       | Ceiling Recessed                                                             |
| CUTOUT SHAPE/SIZE (MM)             | round - 135                                                                  |
| RECESSED DEPTH (MM)                | 130                                                                          |
| THICKNESS OF MOUNTING SURFACE (MM) | max.25                                                                       |
| INGRESS PROTECTION                 | IP20                                                                         |
| WEIGHT (KG)                        | 0.46                                                                         |
| ADJUSTABILITY                      | 0° to 30° swiveling, 355° rotatable                                          |
| INFORMATION                        | Accessories are not applicable with Super Spot except Honeycomb Single use B |
| Electrical info                    |                                                                              |
| CLASS                              | III                                                                          |
| DIM TYPE                           | depending on power supply                                                    |
| ENERGY CLASS                       | F                                                                            |
| Lightsource info                   |                                                                              |
| LIGHTSOURCE NAME                   | LED                                                                          |
| LIGHTSOURCE                        | LED array 5,3W / CRI>90 / 2700K / 557lm                                      |
| TM-30 VALUES                       | rf: 89 / Rg: 100                                                             |
| BEAMANGLE                          | 10°                                                                          |
| LED TECHNICS (LIGHT SOURCE)        | 557lm // 5,3W // 105lm/W                                                     |
| LED TECHNICS (LUMINAIRE)           | 337lm // 6,1W // 55lm/W                                                      |

| Requirements                 |
|------------------------------|
| LED POWER SUPPLY 500 mA - DC |

| Accessories                    |
|--------------------------------|
| COMPO L HONEYCOMB SINGLE USE B |
| COMPO L LINEAR SPREAD LENS     |
| COMPO L SPREAD LENS            |
| COMPO L SOFTENING LENS         |
| COMPO L GLASS SBL              |

For detailed installation instructions, please consult the manual : [9\\_15735\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## COMPO L 92710

9 15735 9210 B

### CEILING COMPATIBILITY

| Ceiling Type                                                                     | Mounting Kit                                                                                                                 |          |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------|
|  |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                  |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |
|  |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                  |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |
|  |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                  |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |

### FINISH YOUR SPECIFICATION

#### LED Power supply

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current


|                   |                                                |      |                      |
|-------------------|------------------------------------------------|------|----------------------|
| <b>15710 3200</b> | LED POWER SUPPLY MULTIPOWER 15W NO DIM 300mA   | 1->2 | <input type="text"/> |
| <b>15710 3600</b> | LED POWER SUPPLY MULTIPOWER 20W NO DIM 500mA   | 1    | <input type="text"/> |
| <b>15710 3700</b> | LED POWER SUPPLY MULTIPOWER 10W DIM8 300mA     | 1    | <input type="text"/> |
| <b>15710 4200</b> | LED POWER SUPPLY MULTIPOWER 20W DIM8 500mA     | 1    | <input type="text"/> |
| <b>15710 4400</b> | LED POWER SUPPLY MULTIPOWER 12W DIM1 300mA     | 1->2 | <input type="text"/> |
| <b>15710 4700</b> | LED POWER SUPPLY MULTIPOWER 20W DIM1 500mA     | 1    | <input type="text"/> |
| <b>15710 5200</b> | LED POWER SUPPLY MULTIPOWER 12W DALI DT6 300mA | 1->2 | <input type="text"/> |
| Dimtype: DALI     |                                                |      |                      |
| <b>15710 5400</b> | LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA | 1    | <input type="text"/> |
| Dimtype: DALI     |                                                |      |                      |

# DELTALIGHT

## COMPO L 92710

9 15735 9210 B

### Mounting kits



**15710 0030 B** MOUNTING KIT COMPO L TRIM B

☐

Cutout dimension (mm): 92



**15710 0060** MOUNTING KIT COMPO L TRIMLESS

☐

Cutout dimension (mm): 92

### Light altering devices

**15710 2100 B** COMPO L HONEYCOMB SINGLE USE B

☐

**15710 2110** COMPO L LINEAR SPREAD LENS

☐

Cutout dimension (mm): 42

**15710 2120** COMPO L SPREAD LENS

☐

Cutout dimension (mm): 42

**15710 2130** COMPO L SOFTENING LENS

☐

Cutout dimension (mm): 42

**15710 2140** COMPO L GLASS SBL

☐

Cutout dimension (mm): 42

Notes: