



INFORM SQ F200-4 92767

25525 9220 B-B



AVAILABLE IN

BLACK-BLACK 25525 9220 B-B

BLACK-FLEMISH GOLD 25525 9220 B-FG

WHITE-BLACK 25525 9220 W-B

WHITE-WHITE 25525 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 400/600mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info




LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 7-11,2W / CRI>90 (R9: 50) / 2700K / 1013-1464lm)
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	2928lm // 22,4W // 131lm/W
LED TECHNICS (LUMINAIRE)	2556lm // 25,8W // 99lm/W

Requirements

INFORM POWER SUPPLY 25W

For detailed installation instructions, please consult the manual : [25525_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 25510 0070 INFORM POWER SUPPLY 50W		1
Dimtype: non-dimmable		
 25510 0395 INFORM POWER SUPPLY 25W DIM5		1
Dimtype: DALI		
 25510 0440 INFORM POWER SUPPLY 25W		1
Dimtype: non-dimmable		

Notes: