




FRAGMA M SUPERSPOT 9308 ADM
WD

23615 931W B

AVAILABLE IN
NOIR 23615 931W B
BLANC 23615 931W W



 [View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Rail Monté sur rail
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	0° à 90° inclinable, 355° rotatif
INFORMATION	4 x LENS SP-8° INCLDIMMABLE LED POWER SUPPLY 900mA-DC 3F MULTI ADAPTER

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	WDL = dimmable sans fil
ENERGY CLASS	E
CERTIFICATION	CB, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 10,4W / CRI>90 (R9: 64) / 3000K / 1180lm
RVALUES	Rf: 92 / Rg: 99
SDMC	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	8°
LED TECHNICS (LIGHT SOURCE)	1180lm // 10,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	1054lm // 12W // 88lm/W


Requirements	
TRACK 3F DIM	

Accessories	
FRAGMA 3X3 HONEYCOMB	

For detailed installation instructions, please consult the manual : [23615_XXXW_HAND.pdf](#)

FINISH YOUR SPECIFICATION

modifier les dispositifs de lumière



23613 0230 B FRAGMA M HONEYCOMB B



COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	

Notes: