





M20/M26H - SPY 66 92718 DIM5

23328 9215 W

AVAILABLE IN  
**BLACK** 23328 9215 B  
**WHITE** 23328 9215 W



 [View on website](#)



| General info       |                                                                                             |
|--------------------|---------------------------------------------------------------------------------------------|
| LOCATION           | indoor                                                                                      |
| INSTALLATION       | Low voltage systems Low voltage system mounted                                              |
| INGRESS PROTECTION | IP20                                                                                        |
| WEIGHT (KG)        | 0.6                                                                                         |
| ADJUSTABILITY      | 0° to 90° swiveling, 355° rotatable                                                         |
| INFORMATION        | REFLECTOR SP-18°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 30° & 45° available |

| Electrical info |                    |
|-----------------|--------------------|
| ELECTRICAL      | 48V-DC             |
| CLASS           | III                |
| DIM TYPE        | DALI               |
| ENERGY CLASS    | E                  |
| CERTIFICATES    | CB, ENEC, EPD, LCA |

| Lightsource info            |                                                  |
|-----------------------------|--------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                              |
| LIGHTSOURCE                 | LED array 25W / CRI>90 (R9: 60) / 2700K / 2688lm |
| TM-30 VALUES                | rf: 89 / Rg: 100                                 |
| SDCM                        | SDCM1                                            |
| RISKGROUP                   | RG1                                              |
| LM80                        | L90B10 > 50000                                   |
| BEAMANGLE                   | 18°                                              |
| LED TECHNICS (LIGHT SOURCE) | 2688lm // 25W // 108lm/W                         |
| LED TECHNICS (LUMINAIRE)    | 1920lm // 28,8W // 67lm/W                        |

| Remarks                                                    |
|------------------------------------------------------------|
| Take a look at our <a href="#">MAGNETIC PROFILES</a> movie |

| Requirements                           |
|----------------------------------------|
| SPY 66 TUBE<br>LED POWER SUPPLY 48V-DC |

| Accessories  |
|--------------|
| HONEYCOMB 57 |

M20/M26H - SPY 66 92718 DIM5

23328 9215 W

For detailed installation instructions, please consult the manual : [23328\\_XXX5\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION


| LED power supplies                                                                                                                                                                                                                                                                                              |   | # of Fixtures             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---------------------------|
| <div><div><div></div><div></div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |   | Min current   Max current |
| <div><div><div><div><div></div><div></div></div><div>5510090</div></div></div><div><div>300 89 48 100</div><div>LED POWER SUPPLY 48V-DC / 100W DIN</div><div>Dimtype: non-dimmable</div></div></div>                                                                                                            | 3 | <div></div>               |
| <div><div><div><div><div></div><div></div></div><div>63114125</div></div></div><div><div>300 89 48 240</div><div>LED POWER SUPPLY 48V-DC / 240W DIN</div><div>Dimtype: non-dimmable</div></div></div>                                                                                                           | 8 | <div></div>               |
| <div><div><div><div><div></div><div></div></div><div>1729830</div></div></div><div><div>21012 0230</div><div>LED POWER SUPPLY 48V-DC / 100W</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div></div>                                                                               | 3 | <div></div>               |
| <div><div><div><div><div></div><div></div></div><div>2239230</div></div></div><div><div>21012 0240</div><div>LED POWER SUPPLY 48V-DC / 200W</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div></div>                                                                               | 7 | <div></div>               |
| Light altering devices                                                                                                                                                                                                                                                                                          |   |                           |
| <div><div><div><div><div></div><div></div></div><div>Ø5714</div></div></div><div><div>24611 0150 B</div><div>HONEYCOMB 57 SINGLE USE B</div></div></div>                                                                                                                                                        |   | <div></div>               |

# DELTALIGHT

## M20/M26H - SPY 66 92718 DIM5

23328 9215 W

### Finish your product



**24611 0100 B** SPY 66 TUBE B

☐

**24611 0100 FBR** SPY 66 TUBE FBR

☐

**24611 0100 FG** SPY 66 TUBE FG

☐

**24611 0100 GC** SPY 66 TUBE GC

☐

**24611 0100 W** SPY 66 TUBE W

☐

### Replaceable reflector / lens



**24611 0220** SPY 66 REFLECTOR 18°

☐

**24611 0230** SPY 66 REFLECTOR 30°

☐

**24611 0240** SPY 66 REFLECTOR 45°

☐

## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H + SBL

### Available Colours





**30411 9205** SHIFTLINE M26H + SBL 2m DIM5



# DELTALIGHT





## M20/M26H - SPY 66 92718 DIM5

23328 9215 W

|                                                                                    |                                                |                                                                                       |
|------------------------------------------------------------------------------------|------------------------------------------------|---------------------------------------------------------------------------------------|
|   | <b>30411 9305</b> SHIFTLINE M26H + SBL 2m DIM5 |    |
|   | <b>30412 9205</b> SHIFTLINE M26H + SBL 3m DIM5 |    |
|   | <b>30412 9305</b> SHIFTLINE M26H + SBL 3m DIM5 |    |
|    | <b>30413 9205</b> SHIFTLINE M26H + SBL 4m DIM5 |    |
|  | <b>30413 9305</b> SHIFTLINE M26H + SBL 4m DIM5 |  |

### SHIFTLINE M26H profile

### Available Colours

|                                                                                     |                                       |                                                                                       |
|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|
|  | <b>23359 0000</b> SLM26H - PROFILE    |  |
|  | <b>23359 0010</b> SLM26H - PROFILE 1m |  |
|  | <b>23359 0020</b> SLM26H - PROFILE 2m |  |
|  | <b>23359 0030</b> SLM26H - PROFILE 3m |  |

# DELTALIGHT

## M20/M26H - SPY 66 92718 DIM5

23328 9215 W

SPLITLINE M20 ST profile

Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: