



## DEEP RINGO TRIMLESS SOFT 93045

19436 9030 BRBB

AVAILABLE IN

**BLACK** 19436 9030 B  
**BRUSHED ALU** 19436 9030 BRA  
**BRUSHED ANTHRACITE** 19436 9030 BRAT  
**BRUSHED BROWN BRONZE** 19436 9030 BRBB  
**BRUSHED COPPER** 19436 9030 BRCU  
**BRUSHED GOLD** 19436 9030 BRG  
**BRUSHED OLD BRONZE** 19436 9030 BROB  
**CREAM** 19436 9030 CR  
**FLEMISH BRONZE** 19436 9030 FBR  
**FLEMISH GOLD** 19436 9030 FG  
**GOLD COLOURED** 19436 9030 GC  
**PIANO BLACK** 19436 9030 PB  
**WHITE** 19436 9030 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - Ø KIT
<b>RECESSED DEPTH (MM)</b>	95
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.2
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR WFL-45° EXCL.DIMMABLE LED POWER SUPPLY 500mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC, EPD, LCA

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
<b>SDCM</b>	SDCM2
<b>RISKGROUPE</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	45°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1038lm // 10,2W // 109lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	792lm // 11,7W // 68lm/W

### Requirements

LED POWER SUPPLY 500mA-DC DIM (Remote)  
MOUNTING KIT R82 TRIMLESS O.F.A.  
MOUNTING KIT AIR 101

























# DELTALIGHT

## DEEP RINGO TRIMLESS SOFT 93045

19436 9030 BRBB


For detailed installation instructions, please consult the manual : [19436\\_XXX0\\_HAND.pdf](#)

### CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 <b>System ceiling</b>	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 <b>Plasterboard</b>	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 <b>Stucanet</b>	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 <b>Concrete + plaster</b>	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 <b>Lintel + plaster</b>	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 <b>Hollow-core slab + plaster</b>	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 <b>Ventilation in plasterboard</b>	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	 29810 0010 - MOUNTING KIT SIDE AIR 101	Required
 <b>Ventilation in concrete + plaster</b>	 29810 0210 - MOUNTING KIT TOP AIR 101	Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
 <b>Cold stretched ceiling</b>	 15212 0070 - MOUNTING KIT R82 TRIMLESS CSC	Required
 <b>Warm stretched ceiling</b>	 15212 0150 - MOUNTING KIT R82 TRIMLESS WSC	Required

### FINISH YOUR SPECIFICATION

#### Emergency units



**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27



# DELTALIGHT

## DEEP RINGO TRIMLESS SOFT 93045

19436 9030 BRBB

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2



Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2



Dimtype: DALI

Cutout dimension (mm): 45




**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2



Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

2



Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

3(3)



Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

2(1)



Dimtype: 1-10V or push button

Cutout dimension (mm): 72



**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

2(1)



Dimtype: DALI

Cutout dimension (mm): 72

# DELTALIGHT

## DEEP RINGO TRIMLESS SOFT 93045

19436 9030 BRBB



**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

5(3)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**



**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

1(1)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

1(1)

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**21012 0010** LED POWER SUPPLY MULTI POWER

2

**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

2

**Dimtype: 1-10V**

**Cutout dimension (mm): 54**




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

2

**Dimtype: DALI**

**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

3(3)

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

2

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**




**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**



**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->2


**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**

# DELTALIGHT

## DEEP RINGO TRIMLESS SOFT 93045

19436 9030 BRBB




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

**Dimtype: DALI**

**Cutout dimension (mm): 30**


### Mounting kits



**15212 2000** MOUNTING KIT R82 TRIMLESS O.F.A.

**Cutout dimension (mm): 105**

### Mounting kits stretched ceiling




**15212 0070** MOUNTING KIT R82 TRIMLESS CSC



**15212 0150** MOUNTING KIT R82 TRIMLESS WSC

### Mounting kits side air + light



**29810 0010** MOUNTING KIT SIDE AIR 101

**Cutout dimension (mm): 168**


# DELTALIGHT

## DEEP RINGO TRIMLESS SOFT 93045

19436 9030 BRBB

### Mounting kits top air + light

---




**29810 0210** MOUNTING KIT TOP AIR 101



Cutout dimension (mm): 135

### Mounting kits side air only

---




**29810 0100** MOUNTING KIT SIDE AIR ONLY 1



Cutout dimension (mm): 168

### Mounting kits top air only

---



**29810 0200** MOUNTING KIT TOP AIR ONLY 1



Cutout dimension (mm): 135

### Mounting kits no air

---



**29810 0050** MOUNTING KIT NO AIR 101



Cutout dimension (mm): 168

Notes: