

## ENTERO RD-S TRIMLESS HE 94020




28486 9420 B

AVAILABLE IN

**BLACK** 28486 9420 B

**FULL WHITE** 28486 9420 FW

**GOLD COLOURED** 28486 9420 GC



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - Ø KIT
<b>RECESSED DEPTH (MM)</b>	105
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.25
<b>ADJUSTABILITY</b>	0° to 30° swiveling, 355° rotatable
<b>INFORMATION</b>	LENS FL-20° EXCL.LED POWER SUPPLY 350mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 6W / CRI>90 (R9: 60) / 4000K / 975lm
<b>TM-30 VALUES</b>	rf: 96 / Rg: 99
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	20°
<b>LED TECHNICS (LIGHT SOURCE)</b>	975lm // 6W // 163lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	853lm // 6,9W // 124lm/W

### Remarks

High Efficacy : > 100lm/W

### Requirements

MOUNTING KIT ENTERO ROUND S  
MOUNTING KIT AIR 105  
LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : [28486\\_XXX0\\_HAND.pdf](#)



# DELTALIGHT

## ENTERO RD-S TRIMLESS HE 94020

28486 9420 B


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 90 91** LED POWER SUPPLY 350mA-DC / 15W

2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 40




**300 90 110** LED POWER SUPPLY 350mA-DC / 10W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42




**300 90 116** LED POWER SUPPLY 350mA-DC / 18W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



**21012 0515** LED POWER SUPPLY MULTI POWER DIM5

1(1)

Dimtype: DALI

Cutout dimension (mm): 55




**21012 0520** LED POWER SUPPLY 350mA-DC / 8W

1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 47



**21012 0575** LED POWER SUPPLY MULTI POWER DIM5

2->3(2)

Dimtype: DALI

Cutout dimension (mm): 55

### Mounting kits



**28400 0010** MOUNTING KIT ENTERO RD-S O.F.A.

Cutout dimension (mm): 105



**28500 0220** MOUNTING KIT DEEP ENTERO RD-S TRIMLESS

Cutout dimension (mm): 133


# DELTALIGHT

## ENTERO RD-S TRIMLESS HE 94020

28486 9420 B

### Mounting kits stretched ceiling

---



**28400 0070** MOUNTING KIT ENTERO RD-S CSC




**28400 0130** MOUNTING KIT ENTERO RD-S WSC



### Mounting kits side air + light

---




**29810 0110** MOUNTING KIT SIDE AIR 105

Cutout dimension (mm): 168



### Mounting kits top air + light

---




**29810 0130** MOUNTING KIT TOP AIR 105

Cutout dimension (mm): 135



### Mounting kits side air only

---




**29810 0100** MOUNTING KIT SIDE AIR ONLY 1

Cutout dimension (mm): 168



### Mounting kits top air only

---



**29810 0200** MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135



# DELTALIGHT

## ENTERO RD-S TRIMLESS HE 94020

28486 9420 B

### Mounting kits no air

---



**29810 0120** MOUNTING KIT NO AIR 105



Cutout dimension (mm): 168

Notes: