



SOLI - LINE 110 DOWN 930 Q-DIM

27157 930Q B

AVAILABLE IN
BLACK 27157 930Q B
WHITE 27157 930Q W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	Qbus dim
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 23,4W / CRI>90 (R9: 65) / 3000K / 3000lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3000lm // 23,4W // 128lm/W
LED TECHNICS (LUMINAIRE)	2004lm // 26,9W // 74lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27157_XXXQ_HAND.pdf](#)

DELTALIGHT

SOLI - LINE 110 DOWN 930 Q-DIM

27157 930Q B

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

3


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

9

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

3

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

7


Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m



Notes:

DELTALIGHT

SOLI - LINE 110 DOWN 930 Q-DIM

27157 930Q B