


223 26 93 A

Technical drawing of a rectangular prism (box) with the following dimensions:

- Height: 600
- Top-left edge: 80
- Top-right edge: 70
- Top-right vertical edge: 10
- Bottom-right edge: 40



LOCATIE	buiten
INSTALLATIE	Vloer Opbouw
STOF EN WATERDICHTHEID	IP55
GEWICHT (KG)	1.4
RICHTBAARHEID	niet richtbaar
INFO	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC

INGANGSSPANNING	100-240V / 50-60Hz
KLASSE	II
VOEDING	YES
ENERGIE KLASSE	F
CERTIFICATEN	CB, EAC, ENEC, RCM


	LIGHTSOURCE NAME	LED
	LICHTBRON	LED array 4,1W / CRI>90 / 3000K / 380lm
	SDCM	SDCM2
	RISK-GROEP	RG2 (threshold 0,6m)
	LED TECHNIEK (LICHTBRON)	380lm // 4,1W // 95lm/W
	LED TECHNIEK (TOESTEL)	269lm // 4,7W // 57lm/W

PIN 11
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

Delta Light NV may revise the information and technical data at any time without notice. Version: 29/04/2026

VERVOLLEDIG UW SPECIFICATIE


Waterdichte doorverbindingen



216 12 00 CBOX

☐

Uitsparingsmaat (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Montagemateriaal voor buitenpaaltjes



229 01 11 PIN 11

☐

Notes: