
DELTALIGHT




ELBO SYMMETRIC P 60 930

REFERENCE 223 26 93 A

AVAILABLE IN
ALU GREY 223 26 93 A
BLACK 223 26 93 B





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 4,1W / CRI>90 / 3000K / 380lm
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LED TECHNICS (LIGHT SOURCE)	380lm // 4,1W // 95lm/W
LED TECHNICS (LUMINAIRE)	269lm // 4,7W // 57lm/W

Options

PIN 11
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : **223_26_83_HAND.pdf**


DELTALIGHT

ELBO SYMMETRIC P 60 930

223 26 93 A


FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT



216 12 02 IP68 CONNECTOR 3P

Pins and plates for bollards



229 01 11 PIN 11

Notes: