





INFORM 40 SQ 180 PDS DOWN-UP 93063 DIM5

30724 9335 B-B

AVAILABLE IN

BLACK-BLACK 30724 9335 B-B

WHITE-BLACK 30724 9335 W-B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PRESENCE & DAYLIGHT SENSOR INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm UP (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm Or DOWN: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm
TM-30 VALUES	Rf: 92 / Rg: 100 DOWN: rf: 92 / Rg: 100 UP: rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 3494lm // 24,2W // 145lm/W UP (HO): 3494lm // 24,2W // 145lm/W Or DOWN: 2534lm // 16,3W // 155lm/W UP: 2534lm // 16,3W // 155lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 2417lm // 27,8W // 87lm/W UP (HO): 2301lm // 27,8W // 83lm/W Or DOWN: 1753lm // 18,7W // 94lm/W UP: 1669lm // 18,7W // 89lm/W

INFORM 40 SQ 180 PDS DOWN-UP 93063 DIM5

30724 9335 B-B


Options

CABLE BASE R/S



For detailed installation instructions, please consult the manual : [30724_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	41 203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	41 203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Other

	41 87 7 26510 0010 PDS REMOTE CONTROL	☐
	56 130 7 26510 0020 PDS SENSOR PROGRAMMER	☐

DELTALIGHT

INFORM 40 SQ 180 PDS DOWN-UP 93063 DIM5

30724 9335 B-B

Notes: