


LED POWER SUPPLY 700mA-DC / 36W DIM1

300 90 128



 [Bekijk op website](#)



Image may differ from the actual product

Algemene info	
LOCATIE	binnen
ZAAGMAAT/OPENING (MM)	rond - 54
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.178
INFO	CURRENT CONTROLLED OUTPUT: 700mA / 36W / 51V-DC $\lambda > 0,9$ Inrush current : 5A - 50 μ s @ 230V-AC Max. 50 units on circuit breaker B 16A
Elektrische info	
KLASSE	II
DIM TYPE	1-10V

Voor gedetailleerde montage gegevens, consulteer de handleiding : [300_90_128_HAND.pdf](#)

WAAR GEBRUIKT

321 107 92	SUPERLOOP HC 70 SBL 927
321 107 93	SUPERLOOP HC 70 SBL 930
321 109 92	SUPERLOOP HC 90 SBL 927
321 109 93	SUPERLOOP HC 90 SBL 930
321 207 93	SUPERLOOP HC 70 SPR 930
321 209 93	SUPERLOOP HC 90 SPR 930
321 407 92	SUPERLOOP VR 70 SBL 927
321 407 93	SUPERLOOP VR 70 SBL 930
321 409 92	SUPERLOOP VR 90 SBL 927
321 409 93	SUPERLOOP VR 90 SBL 930
321 507 92	SUPERLOOP VC 70 SBL 927
321 507 93	SUPERLOOP VC 70 SBL 930
321 509 92	SUPERLOOP VC 90 SBL 927
321 509 93	SUPERLOOP VC 90 SBL 930
20561 9200	SUPERLOOP PLUS HC 70 SBL 927
20561 9300	SUPERLOOP PLUS HC 70 SBL 930
20562 9200	SUPERLOOP PLUS HC 90 SBL 927
20562 9300	SUPERLOOP PLUS HC 90 SBL 930
20570 9200	SUPERLOOP HC SBL OVAL S 927
20570 9300	SUPERLOOP HC SBL OVAL S 930
20572 9200	SUPERLOOP SLIM IN 70 SBL 927

DELTALIGHT

LED POWER SUPPLY 700mA-DC / 36W DIM1

300 90 128

20572 9300 SUPERLOOP SLIM IN 70 SBL 930

20573 9200 SUPERLOOP SLIM IN 90 SBL 927

20573 9300 SUPERLOOP SLIM IN 90 SBL 930

20576 9200 SUPERLOOP SLIM OUT 70 SBL 927

20576 9300 SUPERLOOP SLIM OUT 70 SBL 930

20577 9200 SUPERLOOP SLIM OUT 90 SBL 927

20577 9300 SUPERLOOP SLIM OUT 90 SBL 930

20580 9200 SUPERLOOP SLIM DOWN 70 SBL 927

20580 9300 SUPERLOOP SLIM DOWN 70 SBL 930

Notes: