
DELTALIGHT




# SOLI - FORM 90 92767 DIM5

**REFERENCE** 27131 9225 B-B

AVAILABLE IN
**BLACK-BLACK** 27131 9225 B-B
**BLACK-FLEMISH GOLD** 27131 9225 B-FG
**WHITE-BLACK** 27131 9225 W-B
**WHITE-WHITE** 27131 9225 W-W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.7 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | INCL.36 x REFLECTOR FL-67°<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, LCA |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 16,7W / CRI>90 (R9: 50) / 2700K / 2196lm |
| **TM-30 VALUES** | Rf: 93 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG1 |
| **LM80** | L80 > 60000 |
| **BEAMANGLE** | 67° |
| **LED TECHNICS (LIGHT SOURCE)** | 2196lm // 16,7W // 131lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1917lm // 19,2W // 100lm/W |

**Requirements**

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **27131_XXX5_HAND.pdf**

DELTALIGHT

# SOLI - FORM 90 92767 DIM5

27131 9225 B-B


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 5

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 13


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 5

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**




**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 11


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**


## COMPATIBLE COMPOSABLES

### SOLISCAPE profile

### Available Colours




**27111 0020** SOLI - PROFILE 2m




**27111 0030** SOLI - PROFILE 3m

Notes:

## SOLI - FORM 90 92767 DIM5

27131 9225 B-B