


LED POWER SUPPLY 900mA-DC / 60W DIM5

300 90 129



 [Bekijk op website](#)



Image may differ from the actual product

Algemene info	
LOCATIE	binnen
ZAAGMAAT/OPENING (MM)	rond - 84
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.24
INFO	CURRENT CONTROLLED OUTPUT: 900mA / 60W / 66V-DC $\lambda > 0,9$ Inrush current : 10A - 200 μ s @ 230V-AC Max. 30 units on circuit breaker B 16A
Elektrische info	
KLASSE	II
DIM TYPE	DALI

Voor gedetailleerde montage gegevens, consulteer de handleiding : [300_90_129_HAND.pdf](#)

WAAR GEBRUIKT

321 109 92	SUPERLOOP HC 90 SBL 927
321 109 93	SUPERLOOP HC 90 SBL 930
321 112 92	SUPERLOOP HC 120 SBL 927
321 112 93	SUPERLOOP HC 120 SBL 930
321 209 93	SUPERLOOP HC 90 SPR 930
321 212 93	SUPERLOOP HC 120 SPR 930
321 409 92	SUPERLOOP VR 90 SBL 927
321 409 93	SUPERLOOP VR 90 SBL 930
321 412 92	SUPERLOOP VR 120 SBL 927
321 412 93	SUPERLOOP VR 120 SBL 930
321 509 92	SUPERLOOP VC 90 SBL 927
321 509 93	SUPERLOOP VC 90 SBL 930
321 512 92	SUPERLOOP VC 120 SBL 927
321 512 93	SUPERLOOP VC 120 SBL 930
20562 9200	SUPERLOOP PLUS HC 90 SBL 927
20562 9300	SUPERLOOP PLUS HC 90 SBL 930
20563 9200	SUPERLOOP PLUS HC 120 SBL 927
20563 9300	SUPERLOOP PLUS HC 120 SBL 930
20570 9200	SUPERLOOP HC SBL OVAL S 927
20570 9300	SUPERLOOP HC SBL OVAL S 930
20571 9200	SUPERLOOP HC SBL OVAL M 927

DELTALIGHT

LED POWER SUPPLY 900mA-DC / 60W DIM5

300 90 129

20571 9300	SUPERLOOP HC SBL OVAL M 930
20573 9200	SUPERLOOP SLIM IN 90 SBL 927
20573 9300	SUPERLOOP SLIM IN 90 SBL 930
20574 9200	SUPERLOOP SLIM IN 120 SBL 927
20574 9300	SUPERLOOP SLIM IN 120 SBL 930
20577 9200	SUPERLOOP SLIM OUT 90 SBL 927
20577 9300	SUPERLOOP SLIM OUT 90 SBL 930
20578 9200	SUPERLOOP SLIM OUT 120 SBL 927
20578 9300	SUPERLOOP SLIM OUT 120 SBL 930
20582 9200	SUPERLOOP SLIM DOWN 120 SBL 927
20582 9300	SUPERLOOP SLIM DOWN 120 SBL 930

Notes: