



MONO II



Mono is a well-known member of the Delta Light outdoor range. It's been available in LED for a while and now has additional enhancements with the new Mono II. Mono is the first outdoor wall fixture to combine the Delta Light LED array with a lens, resulting in a far-reaching and strongly delineated lighting effect. The Mono's timeless and sharp contoured design adds a contemporary touch to any facade.

Specification	
Adjustability:	Fixed
Rating:	IP54

Performance	
CRI:	90
*MONO II SP:	7.1W
*MONO II DOWN-UP SP:	2 x 7.1W

Delivered Lumens	3000K	3500K
MONO II:	660Lm	681Lm
MONO II DOWN-UP:	1321Lm	1361Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: MNO-SPDN35FX-N-PXINCD1-UNV

	-				-			
Luminaire	Downlight*	Uplight*	CCT	Function	Finish	Installation	Application	Controls***
MNO MONO II	SP Standard Power	DN Downlight only, no uplight DU Downlight with uplight added	30 3000K 35 3500K	FX Fixed, Exterior Use	A Alu Grey N Dark Grey	MK Mud kit into drywall over 4" junction box PX Coverplate for 4" junction box in corresponding finish NA No optional accessory; utilizing 1/2" EMT install	REM Integral Power Supply	ND-120 Non-Dim 120V D1-UNV 0-10V Dim 120-277V D8-120 FE ELV dim 120V

*** Contact factory for additional dimming options


Related Products

MOMBA, TOPIX X, MONTUR, TIGA X



Finish Options

MONO II DOWN



ALU GREY



DARK GREY

MONO II DOWN-UP




ALU GREY




DARK GREY


MK - MUD KIT 1



PX - COVERPLATE S 121


Dark Grey or ALU Grey
For Trim Style D

PX - COVERPLATE S 122


Dark Grey or ALU Grey
For Trim Style DU

Photometric Options

MONO II DOWN



MONO II DOWN-UP




Driver Options

Remote Driver

A: 8" x B: 2"-1/2 x C: 2"-1/2
A: 203mm x B: 64mm x C: 64mm


- For Remote application
- ETL Listed
- Damp rated



Remote Driver (With Controls ND)

A: 12" x B: 2"-7/8 x C: 4"-1/4
A: 305mm x B: 72mm C: 108mm

- For Remote application
- ETL Listed
- Damp rated





Driver Options

D1

- Dimming Control 0-10 V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

ND

- Dimming Control NON DIMMABLE
- Power Factor @ Full Load >0.95
- Efficiency @ Full Load ≥90
- THD @ Full Load <10%

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.