DELTALIGHT





Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 180 PDS DOWN-UP 94063 DIM5

REFERENCE 30724 9435 B-B

AVAILABLE IN
BLACK-BLACK 30724 9435 B-B
WHITE-BLACK 30724 9435 W-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PRESENCE & DAYLIGHT SENSOR INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm² 1,6m

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm UP (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm Or DOWN: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 3642lm // 24,2W // 151lm/W UP (HO): 3642lm // 24,2W // 151lm/W Or DOWN: 2643lm // 16,3W // 162lm/W UP: 2643lm // 16,3W // 162lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 2520lm // 27,8W // 91lm/W UP (HO): 2398lm // 27,8W // 86lm/W Or DOWN: 1829lm // 18,7W // 98lm/W UP: 1741lm // 18,7W // 93lm/W

Options

CABLE BASE R / S

DELTALIGHT


INFORM 40 SQ 180 PDS DOWN-UP 94063 DIM5

30724 9435 B-B

For detailed installation instructions, please consult the manual : **30724_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐




203 99 56 ANO CABLE BASE S ANO ☐


203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Other



26510 0010 PDS REMOTE CONTROL ☐



26510 0020 PDS SENSOR PROGRAMMER ☐

INFORM 40 SQ 180 PDS DOWN-UP 94063 DIM5

30724 9435 B-B

Notes: